

Approved for Zone 0 locations.

The multi-function Survivor Pivot features a dual beam and 90-degree articulating head. Its spot beam uses a cool white, high-power LED for maximum distance illumination and its flood beam is angled downward for area illumination.



Option with magnet available  
(as shown to the right below)



Strong spring-loaded clip securely grabs onto belts and gear; D-ring provides forward-hanging orientation



- Survivor Pivot securely locks into the charger
- Quick release latch for one-handed grab-and-go
- Easy to remove with gloved hands



<b>Spot:</b> High: 300 lumens; 369m beam distance; runs 4.25 hours (Li-Ion); runs 5.5 hours (alk) Low: 70 lumens; 184m beam distance; runs 16 hours (Li-Ion); runs 15 hours (alk)	
<b>Flood:</b> High: 300 lumens; 35m beam distance; runs 4.25 hours (Li-Ion); runs 5.5 hours (alk) Low: 70 lumens; 17m beam distance; runs 16 hours (Li-Ion); runs 15 hours (alk)	
<b>Combo:</b> High: 325 lumens; 276m beam distance; runs 3.75 hours (Li-Ion); runs 4.5 hours (alk) Low: 80 lumens; 141m beam distance; runs 13 hours (Li-Ion); runs 12 hours (alk)	
Uses rechargeable lithium-ion battery pack (charges in 5 hours) or three (3) AA alkaline batteries (requires optional battery carrier)	
Non-Magnet: Li-Ion: 16.2 oz (459 g) Alkaline: 16.7 oz (473 g) Magnet: Li-Ion: 17.6 oz (499 g) Alkaline: 18.1 oz (513 g)	
Height: 7.93 in (20.14 cm); Width: 2.86 in (7.26 cm) Thickness: 3.29 in (8.36 cm); Thickness (w/ magnet): 3.64 in (9.25 cm)	

Unbreakable polycarbonate lens with scratch-resistant coating		
ATEX / IECEx: II 1G Ex ia op is IIC T3/T4 Ga CE: Meets applicable European Community Directives Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018) Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position		
IP67-rated; dust-tight and waterproof to 1m for 30 minutes		
Limited Lifetime Warranty Visit <a href="http://streamlight.com">streamlight.com</a> for full warranty information		
Description	Orange w/o Magnet	Orange w/ Magnet
Survivor Pivot ATEX - 230V AC/12V DC	91823	91836
Survivor Pivot ATEX - 240V AC/12V DC	91824	91837
Survivor Pivot ATEX - 100V AC/12V DC	91822	91835
Survivor Pivot ATEX - Alkaline	91820	91827