

E-FLOOD® LITEBOX® // E-FLOOD® FIREBOX®

RECHARGEABLE LED LANTERN

DESCRIPTION:	The E-Flood [®] LiteBox [®] and FireBox [®] deliver 1,500 lumens and 4,700 candela of diffused light. The lithium-ion battery provides enhanced performance in a lightweight device. The large tactile push-button switch (with built-in battery status indicator) and a large grip area make this lantern easy to use, even with gloved hands. This light is also easy to carry, whether it's by hand or with the heavy-duty shoulder strap. The articulating head and ability to stand the light upright allows the user to aim light right where it's needed. The E-Flood [®] models use four (4) LEDs with shallow reflectors for a widened beam pattern. The LiteBox [®] is also available in a Power Failure version.		
CASE MATERIAL:	High-impact ABS thermoplastic.		
DIMENSIONS:	Length: 11.2 in (28.4 cm) Width: 5.0 in (12.7 cm) Height: 6.4 in (16.3 cm)		
WEIGHT:	3.1 lbs. (1389 g)		
LENS:	Unbreakable polycarbonate with scratch-resistant coating.		
LIGHT SOURCE:	Four (4) high-power LEDs, impervious to shock with a 50,000-hour lifetime. Two (2) ultra-bright blue taillight LEDs (FireBox $^{\circ}$ models only).		
LIGHT OUTPUT:	See chart. Optimized electronics provide regulated intensity.		
ON/OFF:	Push-button with integrated battery charge indicator. Press and hold to cycle through the different modes.		
RUN TIME:	See chart.		
BATTERY:	Lithium-ion 7.4V, 5200 mAh with onboard safety control, rechargeable up to 500 times. Recharges in 5 hours with provided power supplies. Red and green LEDs in the push-button indicate battery status. When operating, flashing red indicates charging is needed. When charging, green indicates fully charged.		
FEATURES:	Cool white LED technology for extreme brightness. IPX4-rated design. 1-meter impact resistance tested. Serialized for positive identification.		
	 Models: Available in international safety orange or high-visibility yellow. <u>Vehicle Mount E-Flood LiteBox System:</u> Includes shoulder strap and vehicle-mountable hard-wired rack. <u>Vehicle Mount E-Flood FireBox System:</u> Vehicle Mount E-Flood LiteBox system plus two (2) user-programmable ultra-bright blue taillight LEDs. <u>Standard E-Flood LiteBox System:</u> Includes shoulder strap, AC and DC charge cords, and charge rack. <u>Standard E-Flood FireBox System:</u> Standard E-Flood LiteBox system plus two (2) user-programmable ultra-bright blue taillight LEDs. <u>Power Failure E-Flood LiteBox System:</u> Includes shoulder strap, AC and DC charge cords, and charge rack plus trapht blue taillight LEDs. <u>Power Failure E-Flood LiteBox System:</u> Includes shoulder strap, AC and DC charge cords, and charge rack plus "smart" power failure circuitry that automatically turns the lantern on when the power goes off. 		
WARRANTY:	Streamlight's Limited Lifetime Warranty		
APPROVALS:	CE K Meets applicable United Kingdom and European Community Directives. NFPA Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position. © CEC Compliant.		
OPTIONAL ACCESSORIES:	100V, 120V, 230V, or 240V AC (home) and 12VDC (automobile) charge cords, hands-free shoulder strap (included with standard + VM models), locking charge rack, quick-release shoulder/waist strap		

	FL 1 Standard	HIGH	LOW
OUTPUT	Jul .	1500	350
001101	4 1	LUMENS	LUMENS
RUN TIME	\bigcirc	7h 30min	17h 45min
DISTANCE		137m	63m
INTENSITY		4,700cd	1,000cd