

PRODUCT FACT SHEET

Enduro® ULTRA COMPACT LED HEADLIGHT

MARKET APPLICATIONS:	Hardware/Tool, Industrial, Law Enforcement, Security, Automotive, Sporting Goods, Consumer.		
DESCRIPTION:	The Enduro [®] is the most compact, lightweight, high performance, ergonomically developed LED headlight on the market today. At only 2.75 ounces with batteries, this headlight uses (2) 1.5V "AAA" batteries for a combined performance at the top of the sub compact headlight category. The light has been specifically engineered to minimize weight and maximize run time. The lights optimized center of gravity provides maximum wearer comfort and stability during use and the integral hat clip allows the light to be attached to the brim of a hat or on the wearers shirt or jacket without the need for the head strap. This headlight offers High and Low lighting modes, and is packaged with "Rubber/Elastic Combo" head strap. The Enduro [®] is available in black and REALTREE HARDWOODS Green High Definition (HD) camouflage.		
CASE MATERIAL:	Impact resistant ABS; case and integral hat clip		
DIMENSIONS:	Face cap diameter 1.30 in. (3.25 cm) Maximum headlight width: 2.25 in. (5.70 cm) Maximum Headlight depth: 1.60 in. (4.0 cm) -including head strap and mounting plate		
WEIGHT:	2.75 oz (78.5 grams) - weight with batteries and head strap		
LENS:	Unbreakable polycarbonate lens		
LIGHT SOURCE:	C4 $^{\odot}$ LED technology, impervious to shock with a 50,000 hour lifetime		
LIGHT OUTPUT:	See chart.		
ON/OFF:	Push button switch; 1 st mode: Low, 2 nd mode: High		
RUN TIME:	See Chart. All runtime claims are to 10% of initial lumen output.		
BATTERY:	Two (2) 1.5V AAA cells - included in package		
	C4 [®] LED technology for extreme brightness. IPX7 rated for water proof operation. All openings o-ring sealed. 2 meter impact resistance tested. Solid State Power Regulation provides maximum light output throughout battery life. Integral Hat Clip		
APPROVALS:	CE Meets applicable European Community Directives.		
WARRANTY:	Streamlight's Limited Lifetime Warranty		
OPTIONAL ACCESSORIES:	None		

OUTPUT	FL1 STANDARD	HIGH 50 LUMENS	LOW 10 LUMENS
RUNTIME	(L)	5.5h	25h
DISTANCE		66 m	33m
INTENSITY		1,100cd	285cd