



PRODUCT FACT SHEET

PROTAC® RAIL MOUNT 1

DESCRIPTION:	Lightweight, low-profile, gun-mounted tactical light powered by CR123A lithium or AA batteries. The CR123A battery provides 1.75 hours of continuous run time on high and 14.5 hours on low. The rail clamp is designed to securely attach/detach from rifles, carbines, and submachine guns with a MIL-STD-1913 rail. The included M-LOK® mount allows for alternative mounting options to M-LOK and M-LOK compatible rail systems.				
CASE MATERIAL:	6000 Series machined aircraft aluminum with black anodized finish				
DIMENSIONS:	Length: 4.25 in (10.8 cm)	Width: 1.20 in (3.04 cm)	Height: 1.50 in (3.81 cm)		
WEIGHT:	4.3 oz (121.9 g) with CR123A battery (included in purchase) 4.5 oz (127.5 g) with AA alkaline battery (included in purchase)				
LENS:	High-temperature, shock-mounted, AR coated, impact-resistant BOROFLOAT® glass				
LIGHT SOURCE:	White LED impervious to shock with a 50,000-hour lifetime				
LIGHT OUTPUT:	CR123A:	High - 350 lumens; 12,000 candela peak beam intensity; 219 m beam distance Low - 40 lumens; 1,380 candela peak beam intensity; 19 m beam distance			
	AA Alkaline/Lithium:	High - 150 lumens; 4,950 candela peak beam intensity; 141 m beam distance Low - 40 lumens; 1,380 candela peak beam intensity; 19 m beam distance			
	TIR optic produces a concentrated beam with optimum peripheral illumination.				
ON/OFF:	Multi-function, push-button tactical tail switch or remote pressure switch with latching push-button and momentary pad. One-handed operation of momentary, variable intensity, or strobe mode. TEN-TAP® programmable switch to allow for user selection of one of three different programs: high/strobe (factory default), high only, or low/high.				
RUN TIME:	CR123A: High - 1.75 hours; Low - 14.5 hours AA Alkaline: High - 1.5 hours; Low - 8 hours AA Lithium: High - 4.5 hours; Low - 14 hours Run times are to 10% of initial output. Solid-state current regulation for consistent illumination level.				
BATTERY:	One (1) 3-volt CR123A lithium battery (with a storage life of 10 years), one (1) AA alkaline battery, or one (1) AA lithium battery				
FEATURES:	Push-button tail switch features momentary/constant on operation One-handed snap-on and tighten interface keeps hands away from muzzle when attaching/detaching Securely fits a broad range of weapons Mounts directly to guns with MIL-STD-1913 (Picatinny) rails or M-LOK and M-LOK compatible rail systems Extensively live fire tested, impact-resistant construction IPX7-rated with standard push-button switch installed; waterproof to 1 meter for 30 minutes IPX4-rated with remote pressure switch installed				
APPROVALS:	UK Meets applicable United Kingdom and European Community Directives CEC Compliant				
WARRANTY:	Streamlight's Limited Lifetime Warranty				
OPTIONAL ACCESSORIES:	Red, blue, and green filters				

All rights reserved. M-LOK® is a registered trademark of Magpul Industries Corp. BOROFLOAT® is a registered trademark of SCHOTT AG.