

**PRODUCT FACT SHEET** 

## $\frac{TLR-2^{\circ} G}{RAIL MOUNTED STROBING TACTICAL LIGHT WITH GREEN LASER SIGHT}$

<ul> <li>DESCRIPTION: The ultimate in target engagement enhancement, this rugged lithium battery powered LED weapon light with integrated green laser fits most hand guns and long guns. This light/laser comb features a fast and tool-less rail clamp for rock solid repeatability on a wide variety of weapon. 300 lumen output delivers a powerful beam with extensive range, good peripheral coverage and selectable strobe mode. The daylight visible green targeting laser uses the latest direct drive diode that burns brightly in extreme temperatures. Runs for 2.5 hours continuously with both light and laser in operation.</li> <li>CASE MATERIAL: 6000 Series machined aircraft aluminum with black anodized finish on main body. High impact, chemically resistant engineering polymer housing.</li> <li>DIMENSIONS: Length: 3.39 in. (8.61 cm) Width: 1.47 in. (3.73 cm) Height: 1.83 in. (4.64 cm)</li> <li>WEIGHT: 4.72 oz (133.8 grams) with batteries (included in purchase).</li> <li>LENS: High temperature, shock mounted, impact resistant Boro Float glass.</li> <li>LIGHT SOURCE: White C4+ LED technology, impervious to shock with a 50,000 hour lifetime. 510-530nm direct drive green laser with wide operating temperature.</li> <li>LIGHT OUTPUT: 12,000 candela peak beam intensity and 300 lumens measured system output. Textured parabolic reflector produces a concentrated beam with optimum peripheral illumination. Green laser provides high visibility uong-range targeting.</li> <li>ON/OFF: Ambidextrous momentary/steady On-Off switch. Three position Mode Selector switch (Laser only, LED illumination only, both) Double tap of momentary paddle within 0.4 seconds activates strobe. Strobe can be disabled.</li> <li>RUN TIME: 2.5 hours regulated run time when using Laser only. Self or 10 years.</li> <li>FFATURES: C44'LED technology for extreme brightness. High visibility green laser with wide operating temperature. Operating temperature: -40°F to ±120°F. Fits existing weapon holsters made doperating temperatur</li></ul>	MARKET	
<ul> <li>light with integrated green laser fits most hand guns and long guns. This light/laser combo features a fast and tool-less rial clamp for rock solid repeatability on a wide variety of weapons. 300 lumen output delivers a powerful beam with extensive range, good peripheral coverage and selectable strobe mode. The daylight visible green targeting laser uses the latest direct drive diode that burns brightly in extreme temperatures. Runs for 2.5 hours continuously with both light and laser in operation.</li> <li>CASE MATERIAL: 6000 Series machined aircraft aluminum with black anodized finish on main body. High impact, chemically resistant engineering polymer housing.</li> <li>DIMENSIONS: Length: 3.39 in. (8.61 cm) Width: 1.47 in. (3.73 cm) Height: 1.83 in. (4.64 cm)</li> <li>WEIGHT: 4.72 oz (133.8 grans) with batteries (included in purchase).</li> <li>LIGHT SOURCE: White C4*LED technology, impervious to shock with a 50,000 hour lifetime. 510-530nm direct drive green laser with wide operating temperature.</li> <li>LIGHT OUTPUT: 12,000 candela peak beam intensity and 300 lumens measured system output. Textured parabolic reflector providues a concentrated beam with optimum peripheral illumination. Green laser provides high visibility long-range targeting.</li> <li>ON/OFF: Ambidextrous momentary/steady 0.07.0Ff witch. Three position Mode Selector switch (Laser only, LED illumination only, both) bouble tap of momentary paddle within 0.4 seconds activates strobe. Strobe can be disabled.</li> <li>RUN TIME: 2.5 Nours regulated run time when using Laser only. LED simultaneously. 17 hours of run time when using Laser only. Self 10 years.</li> <li>FEATURES: C4*LED technology for extreme brightness. High visibility green laser with wide operating temperature. Operating temperature: -40° F to -120° F. Fits existing weapon holsters made for the TLR-2. Ambidextrous momentary/steady 0.07.0Ff witch. One handed snap-on &amp; tighten interface keeps hands away from muzzle when attaching/detach</li></ul>	APPLICATIONS:	Sporting Goods, Law Enforcement, Security, Home Defense
High impact, chemically resistant engineering polymer housing.DIMENSIONS:Length: 3.39 in. (8.61 cm)Width: 1.47 in. (3.73 cm)Height: 1.83 in. (4.64 cm)WEIGHT:4.72 oz (133.8 grams) with batteries (included in purchase).LENS:High temperature, shock mounted, impact resistant Boro Float glas.LIGHT SOURCE:White C4*LED technology, impervious to shock with a 50,000 hour lifetime. 510-530nm direct drive green laser with wide operating temperature.LIGHT OUTPUT:12,000 candela peak beam intensity and 300 lumens measured system output. Textured parabolic reflector produces a concentrated beam with optimum peripheral illumination. Green laser provides high visibility long-range targeting.ON/OFF:Ambidextrous momentary/steady 0n-Off switch. Three position Mode Selector switch (Laser only, LED illumination only, both) Double tap of momentary paddle within 0.4 seconds activates strobe. Strobe can be disabled.RUN TIME:2.5 hours regulated run time when using Laser /LED simultaneously. 17 hours of run time when using Laser only. Solid-state current regulation for consistent illumination level.BATTERY:Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.FEATURES:C4*LED technology for extreme brightness. High visibility green laser with wide operating temperature. Operating temperature: -40*F to +120*F. Fits existing weapon holsters made for the TLR-2. Ambidextrous momentary/steady On-Off switch. One handed snap-on & tighten interface keeps hands away from muzzle when attaching/detaching. Securely fits a broad range of weapons. Mount directly to handguns with Glock-style rails and to all ML-STD-1913 (Picatinny) rails. Includes keys for Glock-style, Picatinny, Beretta 90two, S&W 9	DESCRIPTION:	light with integrated green laser fits most hand guns and long guns. This light/laser combo features a fast and tool-less rail clamp for rock solid repeatability on a wide variety of weapons. 300 lumen output delivers a powerful beam with extensive range, good peripheral coverage and selectable strobe mode. The daylight visible green targeting laser uses the latest direct drive diode that burns brightly in extreme temperatures. Runs for 2.5 hours continuously with both light and laser
<ul> <li>WEIGHT: 4.72 oz (133.8 grams) with batteries (included in purchase).</li> <li>LENS: High temperature, shock mounted, impact resistant Boro Float glass.</li> <li>LIGHT SOURCE: White C4* LED technology, impervious to shock with a 50,000 hour lifetime. 510-530nm direct drive green laser with wide operating temperature.</li> <li>LIGHT OUTPUT: 12,000 candela peak beam intensity and 300 lumens measured system output. Textured parabolic reflector produces a concentrated beam with optimum peripheral illumination. Green laser provides high visibility long-range targeting.</li> <li>ON/OFF: Ambidextrous momentary/steady On-Off switch. Three position Mode Selector switch (Laser only, LED illumination only, both) Double tap of momentary paddle within 0.4 seconds activates strobe. Strobe can be disabled.</li> <li>RUN TIME: 2.5 hours regulated run time when using Laser /LED simultaneously. 17 hours of run time when using Laser only. Solid-state current regulation for consistent illumination level.</li> <li>BATTERY: Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.</li> <li>FEATURES: C4*LED technology for extreme brightness. High visibility green laser with wide operating temperature. Operating temperature: -40°F to +120°F. Fits existing weapon holsters made for the TLR-2. Ambidextrous momentary/steady On-Off switch. One handed snap-on &amp; tighten interface keeps hands away from muzzle when attaching/detaching. Securely fits a broad range of weapons. Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails. Includes keys for Glock-style, Picatinny, Beretta 90two, 5&amp;W 99, S&amp;W TSW and Sig P320 rails. Extensively live-fire tested impact resistant construction.</li> <li>Windage and Elevation adjustment screws mounted in bushings for long life and dependable zero retention. Highly accurate sight repeatability when remounting. IPX4 rated design for water resistant operation. Strobe can be disabled.</li> <li>APPROVALS: Meets applicable European Community Directives. C</li></ul>	CASE MATERIAL:	•
<ul> <li>LENS: High temperature, shock mounted, impact resistant Boro Float glass.</li> <li>LIGHT SOURCE: White C4* LED technology, impervious to shock with a 50,000 hour lifetime. 510-530nm direct drive green laser with wide operating temperature.</li> <li>LIGHT OUTPUT: 12,000 candela peak beam intensity and 300 lumens measured beam with optimum peripheral illumination. Green laser provides high visibility long-range targeting.</li> <li>ON/OFF: Ambidextrous momentary/steady On-Off switch. Three position Mode Selector switch (Laser only, LED illumination only, both) Double tap of momentary paddle within 0.4 seconds activates strobe. Strobe can be disabled.</li> <li>RUN TIME: 2.5 hours regulated run time when using Laser /LED simultaneously. 17 hours of run time when using Laser only. Solid-state current regulation for consistent illumination level.</li> <li>BATTERY: Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.</li> <li>FEATURES: C4*LED technology for extreme brightness. High visibility green laser with wide operating temperature. Operating temperature: -40° F to +120° F. Fits existing weapon holsters made for the TLR-2. Ambidextrous momentary/steady On-Off switch. One handed snap-on &amp; tighten interface keeps hands away from muzzle when attaching/detaching. Securely fits a broad range of weapons. Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails. Includes keys for Glock-style, Picatinny, Beretta 90two, St&amp; 99, St&amp;W TSW and Sig P320 rails. Extensively live-fire tested impact resistant construction. Windage and Elevation adjustment screws mounted in bushings for long life and dependable zero retention. Highly accurate sight repeatability when remounting. IPX4 rated design for water resistant operation. Strobe can be disabled.</li> <li>APPROVALS: Meets applicable European Community Directives. C€</li> <li>WARRANTY: Streamlight's Limited Lifetime Warranty.</li> <li>OPTIONAL</li> </ul>	DIMENSIONS:	Length: 3.39 in. (8.61 cm) Width: 1.47 in. (3.73 cm) Height: 1.83 in. (4.64 cm)
<ul> <li>LIGHT SOURCE: White C4*LED technology, impervious to shock with a 50,000 hour lifetime. 510-530nm direct drive green laser with wide operating temperature.</li> <li>LIGHT OUTPUT: 12,000 candela peak beam intensity and 300 lumens measured system output. Textured parabolic reflector produces a concentrated beam with optimum peripheral illumination. Green laser provides high visibility long-range targeting.</li> <li>ON/OFF: Ambidextrous momentary/steady On-Off switch. Three position Mode Selector switch (Laser only, LED illumination only, both) Double tap of momentary paddle within 0.4 seconds activates strobe. Strobe can be disabled.</li> <li>RUN TIME: 2.5 hours regulated run time when using Laser/LED simultaneously. 17 hours of run time when using Laser only. Solid-state current regulation for consistent illumination level.</li> <li>BATTERY: Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.</li> <li>FEATURES: C4*LED technology for extreme brightness. High visibility green laser with wide operating temperature. Operating temperature: -40°F to +120°F. Fits existing weapon holsters made for the TLR-2. Ambidextrous momentary/steady On-Off switch. One handed snap-on &amp; tighten interface keeps hands away from muzzle when attaching/detaching. Securely fits a broad range of weapons. Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails. Includes keys for Glock-style, Picatinny, Beretta 90two, 5&amp;W 99, S&amp;W TSW and Sig P320 rails. Extensively live-fire tested impact resistant construction. Windage and Elevation adjustment screws mounted in bushings for long life and dependable zero retention. Highly accurate sight repeatability when remounting. IPX4 rated design for water resistant operation. Strobe can be disabled.</li> <li>APPROVALS: Meets applicable European Community Directives. C€</li> <li>WARRANTY: Streamlight's Limited Lifetime Warranty.</li> <li>OPTIONAL</li> </ul>	WEIGHT:	4.72 oz (133.8 grams) with batteries (included in purchase).
<ul> <li>510-530nm direct drive green laser with wide operating temperature.</li> <li>LIGHT OUTPUT: 12,000 candela peak beam intensity and 300 lumens measured system output. Textured parabolic reflector produces a concentrated beam with optimum peripheral illumination. Green laser provides high visibility long-range targeting.</li> <li>ON/OFF: Ambidextrous momentary/steady On-Off switch. Three position Mode Selector switch (Laser only, LED illumination only, both) Double tap of momentary paddle within 0.4 seconds activates strobe. Strobe can be disabled.</li> <li>RUN TIME: 2.5 hours regulated run time when using Laser /LED simultaneously. 17 hours of run time when using Laser only. Solid-state current regulation for consistent illumination level.</li> <li>BATTERY: Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.</li> <li>FEATURES: C4*LED technology for extreme brightness. High visibility green laser with wide operating temperature. Operating temperature: -40° F to +120° F. Fits existing weapon holsters made for the TLR-2. Ambidextrous momentary/steady On-Off switch. One handed snap-on &amp; tighten interface keeps hands away from muzzle when attaching/detaching. Securely fits a broad range of weapons. Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails. Includes keys for Glock-style, Picatinny, Beretta 90two, S&amp;W 99, S&amp;W TSW and Sig P320 rails. Extensively live-fire tested impact resistant construction. Windage and Elevation adjustment screws mounted in bushings for long life and dependable zero retention. Highly accurate sight repeatability when remounting. IPX4 rated design for water resistant operation. Strobe can be disabled.</li> <li>APPROVALS: Meets applicable European Community Directives. C€</li> <li>WARRANTY: Streamlight's Limited Lifetime Warranty.</li> <li>OPTIONAL</li> </ul>	LENS:	High temperature, shock mounted, impact resistant Boro Float glass.
<ul> <li>Textured parabolic reflector produces a concentrated beam with optimum peripheral illumination. Green laser provides high visibility long-range targeting.</li> <li>ON/OFF: Ambidextrous momentary/steady On-Off switch. Three position Mode Selector switch (Laser only, LED illumination only, both) Double tap of momentary paddle within 0.4 seconds activates strobe. Strobe can be disabled.</li> <li>RUN TIME: 2.5 hours regulated run time when using Laser /LED simultaneously. 17 hours of run time when using Laser only. Solid-state current regulation for consistent illumination level.</li> <li>BATTERY: Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years. FEATURES: C4*LED technology for extreme brightness. High visibility green laser with wide operating temperature. Operating temperature: -40°F to +120°F. Fits existing weapon holsters made for the TLR-2. Ambidextrous momentary/steady On-Off switch. One handed snap-on &amp; tighten interface keeps hands away from muzzle when attaching/detaching. Securely fits a broad range of weapons. Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails. Includes keys for Glock-style, Picatinny, Beretta 90two, S&amp;W 99, S&amp;W TSW and Sig P320 rails. Extensively live-fire tested impact resistant construction. Windage and Elevation adjustment screws mounted in bushings for long life and dependable zero retention. Highly accurate sight repeatability when remounting. IPX4 rated design for water resistant operation. Strobe can be disabled.</li> <li>APPROVALS: Meets applicable European Community Directives. CE WARRANTY: Streamlight's Limited Lifetime Warranty. OPTIONAL</li> </ul>	LIGHT SOURCE:	
Three position Mode Selector switch (Laser only, LED illumination only, both)         Double tap of momentary paddle within 0.4 seconds activates strobe. Strobe can be disabled.         RUN TIME:       2.5 hours regulated run time when using Laser/LED simultaneously. 17 hours of run time when using Laser only. Solid-state current regulation for consistent illumination level.         BATTERY:       Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.         FEATURES:       C4*LED technology for extreme brightness. High visibility green laser with wide operating temperature. Operating temperature: -40° F to +120° F. Fits existing weapon holsters made for the TLR-2. Ambidextrous momentary/steady On-Off switch. One handed snap-on & tighten interface keeps hands away from muzzle when attaching/detaching. Securely fits a broad range of weapons. Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails. Includes keys for Glock-style, Picatinny, Beretta 90two, S&W 99, S&W TSW and Sig P320 rails. Extensively live-fire tested impact resistant construction. Windage and Elevation adjustment screws mounted in bushings for long life and dependable zero retention. Highly accurate sight repeatability when remounting. IPX4 rated design for water resistant operation. Strobe can be disabled.         APPROVALS:       Meets applicable European Community Directives. C€         WARRANTY:       Streamlight's Limited Lifetime Warranty.         OPTIONAL       Lifetime Warranty.	LIGHT OUTPUT:	Textured parabolic reflector produces a concentrated beam with optimum peripheral illumination.
<ul> <li>17 hours of run time when using Laser only. Solid-state current regulation for consistent illumination level.</li> <li>BATTERY: Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.</li> <li>FEATURES: C4°LED technology for extreme brightness. High visibility green laser with wide operating temperature. Operating temperature: -40°F to +120°F. Fits existing weapon holsters made for the TLR-2. Ambidextrous momentary/steady On-Off switch. One handed snap-on &amp; tighten interface keeps hands away from muzzle when attaching/detaching. Securely fits a broad range of weapons. Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails. Includes keys for Glock-style, Picatinny, Beretta 90two, S&amp;W 99, S&amp;W TSW and Sig P320 rails. Extensively live-fire tested impact resistant construction. Windage and Elevation adjustment screws mounted in bushings for long life and dependable zero retention. Highly accurate sight repeatability when remounting. IPX4 rated design for water resistant operation. Strobe can be disabled.</li> <li>APPROVALS: Meets applicable European Community Directives. CE</li> <li>WARRANTY: Streamlight's Limited Lifetime Warranty.</li> </ul>	ON/OFF:	Three position Mode Selector switch (Laser only, LED illumination only, both)
<ul> <li>FEATURES: C4*LED technology for extreme brightness. High visibility green laser with wide operating temperature. Operating temperature: -40°F to +120°F. Fits existing weapon holsters made for the TLR-2. Ambidextrous momentary/steady On-Off switch. One handed snap-on &amp; tighten interface keeps hands away from muzzle when attaching/detaching. Securely fits a broad range of weapons. Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails. Includes keys for Glock-style, Picatinny, Beretta 90two, S&amp;W 99, S&amp;W TSW and Sig P320 rails. Extensively live-fire tested impact resistant construction. Windage and Elevation adjustment screws mounted in bushings for long life and dependable zero retention. Highly accurate sight repeatability when remounting. IPX4 rated design for water resistant operation. Strobe can be disabled.</li> <li>APPROVALS: Meets applicable European Community Directives. CE</li> <li>WARRANTY: Streamlight's Limited Lifetime Warranty.</li> </ul>	RUN TIME:	17 hours of run time when using Laser only.
<ul> <li>High visibility green laser with wide operating temperature.</li> <li>Operating temperature: -40°F to +120°F.</li> <li>Fits existing weapon holsters made for the TLR-2.</li> <li>Ambidextrous momentary/steady On-Off switch.</li> <li>One handed snap-on &amp; tighten interface keeps hands away from muzzle when attaching/detaching.</li> <li>Securely fits a broad range of weapons.</li> <li>Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails.</li> <li>Includes keys for Glock-style, Picatinny, Beretta 90two, S&amp;W 99, S&amp;W TSW and Sig P320 rails.</li> <li>Extensively live-fire tested impact resistant construction.</li> <li>Windage and Elevation adjustment screws mounted in bushings for long life and dependable zero retention.</li> <li>Highly accurate sight repeatability when remounting.</li> <li>IPX4 rated design for water resistant operation.</li> <li>Strobe can be disabled.</li> </ul> APPROVALS: Meets applicable European Community Directives. <b>C</b>	BATTERY:	Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.
<ul> <li>APPROVALS: Meets applicable European Community Directives. CE</li> <li>WARRANTY: Streamlight's Limited Lifetime Warranty.</li> <li>OPTIONAL</li> </ul>	FEATURES:	<ul> <li>High visibility green laser with wide operating temperature.</li> <li>Operating temperature: -40°F to +120°F.</li> <li>Fits existing weapon holsters made for the TLR-2.</li> <li>Ambidextrous momentary/steady On-Off switch.</li> <li>One handed snap-on &amp; tighten interface keeps hands away from muzzle when attaching/detaching.</li> <li>Securely fits a broad range of weapons.</li> <li>Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails.</li> <li>Includes keys for Glock-style, Picatinny, Beretta 90two, S&amp;W 99, S&amp;W TSW and Sig P320 rails.</li> <li>Extensively live-fire tested impact resistant construction.</li> <li>Windage and Elevation adjustment screws mounted in bushings for long life and dependable zero retention.</li> <li>Highly accurate sight repeatability when remounting.</li> <li>IPX4 rated design for water resistant operation.</li> </ul>
WARRANTY: Streamlight's Limited Lifetime Warranty. OPTIONAL	APPROVALS:	
OPTIONAL		
	OPTIONAL	

EXPORT CONTROLS: The export of this product is subject to the jurisdiction of the U.S. Department of Commerce Export Administrative Regulations ("EAR"). The exported sale, transfer or shipment of this product is expressly prohibited by U.S. Law and is subject to export restrictions, including export licenses and accompanying documentation and authorization, the absence of which may result in fines and penalties. Furthermore, diversion, resale, re-export or transfer of this product is contrary to U.S. Law and is prohibited without the prior written consent of the U.S. Department of Commerce. Compliance with any and all export controls are the sole responsibility of the distributor. Issued: 12/14/2012