## STREMUIGHT.

## PRODUCT FACT SHEET

## TL-RACKER®

## SHOTGUN FOREND LIGHT FOR MOSSBERG® & REMINGTON® PUMP-ACTION SHOTGUNS

**DESCRIPTION:** The lightweight, all-in-one TL-Racker® shotgun forend tactical light features the latest in high-

power LED technology, providing 1,000 lumens and 1.5 hours of continuous run time. The TL-Racker® is designed to easily replace the original factory forend of a 12-gauge Mossberg $^{\circ}$  500 $^{\circ}$  or 590 $^{\circ}$  with a 7  $^{3}$ 4" action slide, 12-gauge Mossberg $^{\circ}$  590 $^{\circ}$  Shockwave or Mossberg 500 $^{\circ}$  or 590 $^{\circ}$  with a

6 ¾" action slide, or 12-gauge Remington® 870 and TAC-14 model pump-action shotguns\*,

depending on model. Unscrew the action slide nut to replace the forend (wrench included). O-ring

and gasket-sealed.

**CASE MATERIAL:** Body: Impact modified engineering polymer with textured grip, available in black.

Models are also available in orange for "less lethal" applications.

Face Cap: 6000 series machined aircraft aluminum with black anodized finish.

Strap: High-strength polyester; black (Shockwave model only).

**DIMENSIONS:** Length: 8.00 in (20.32 cm) Width: 1.95 in (4.95 cm) Grip Height: 2.64 in (6.71 cm)

**WEIGHT:** 12.1 oz (343 g) with batteries (included with purchase).

**LENS:** High temperature, shock-mounted, impact-resistant BOROFLOAT® glass; gasket-sealed.

**LIGHT SOURCE:** High-power white LED, impervious to shock with a 50,000-hour lifetime.

**LIGHT OUTPUT:** 1,000 lumens, 20,000 candela peak beam intensity, and 283m beam distance.

TIR optic produces a concentrated beam with optimum peripheral illumination.

Optimized electronics provide regulated intensity.

**ON/OFF:** Ambidextrous, dual elongated switch pad design with momentary/constant on operation.

**RUN TIME:** 1.5 hours regulated run time to the 10% output level.

**BATTERY:** (2) 3-volt CR123A lithium batteries with a storage life of 10 years.

**FEATURES:** High-power LED for extreme brightness.

Ambidextrous, elongated switch pad with momentary/constant on operation.

Forend wrench included.

Operating temperature: -20°F to +120°F. IPX7-rated design; waterproof operation. Serialized for positive identification.

WARRANTY: Streamlight's Limited Lifetime Warranty

**OPTIONAL** 

ACCESSORIES: N/A

\*Note: The TL-Racker will <u>not</u> fit Mossberg® FLEX models regardless of action slide length or Remington® 870 Super Magnum models.

All Rights Reserved. Mossberg®, 500®, and 590® are registered trademarks of O.F. Mossberg and Sons, Inc. Streamlight has not sought endorsement of this product from O.F. Mossberg and Sons, Inc. Remington® is a registered trademark of Ammunition Operations, LLC. Streamlight has not sought endorsement of this product from Ammunition Operations, LLC. BOROFLOAT® is a registered trademark of SCHOTT AG.

Issued: 1/18/2019

Revised: 9/19/2024 Rev: 3 Assembled in the USA. Document #333