

PRODUCT FACT SHEET

TLR-9[®] RAIL MOUNTED TACTICAL LIGHT

MARKET

APPLICATIONS: Law Enforcement, Security, Sporting Goods, Consumer

DESCRIPTION: Lightweight & compact, the TLR-9® full frame Weapon-Mounted Tactical Light features the latest

in LED technology for high lumen operation and provides 1.5 hours of continuous runtime from a two CR123 lithium batteries. 1000 lumen output delivers a powerful beam with extensive range, good peripheral coverage and selectable strobe mode. The TLR-9® model features rear switches.

Rail clamp designed to rapidly attach/detach from side of weapon.

CASE MATERIAL: Body and Facecap: 6000 Series machined aircraft aluminum with black anodized finish.

Switch housing: Impact and chemical resistant engineered polymer.

DIMENSIONS: Width: 1.18 in. (2.98 cm) Height: 1.27 (3.22 cm) Length: 3.87 in. (9.82 cm)

WEIGHT: 4.26 oz. (120.9 grams) with (2) batteries (included with purchase).

LENS: High temperature, shock mounted, impact resistant Borofloat® glass.

LIGHT SOURCE: LED, white, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: 1000 lumens, 10,000 candela peak beam intensity and 200 m beam distance.

Custom TIR optic produces a concentrated beam with optimum peripheral illumination.

Optimized electronics provide regulated intensity.

ON/OFF: TLR-9®: Rear switches left and right of trigger guard provide ambidextrous operation available

with high and low actuators.

Quick press for constant on operation and press and hold for momentary operation.

Double tap either switch within ¼ second activates strobe (if enabled).

RUN TIME: 1.5 continuous hours to the 10% output level. 3 continuous hours on strobe.

BATTERY: Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.

FEATURES: Lightweight and compact.

High power LED for extreme brightness.

Ambidextrous operation.

One handed snap-on and tighten interface keeps hands away from muzzle when attaching or

detaching.

Securely fits a broad range of weapons using key kit provided.

Extensively live-fire tested.

Operating temperature: -40°F to +120°F.

IPX7 rated design; waterproof to 1 meter for 30 minutes.

Serialized for positive identification.

APPROVALS: CE Meets applicable European Community Directives.

WARRANTY: Streamlight's Limited lifetime warranty.

OPTIONAL

ACCESSORIES: Mounting adapters

Borofloat® is a registered trademark by a company of the Schott group.

Issued: 12/20/2019

Revised: 05/04/2021 Rev: 1 Assembled In The USA. Document #346