

## VULCAN® 180 HAZ-LO®

## DIV. 1 INTRINSICALLY SAFE RECHARGEABLE LANTERN

DESCRIPTION:	The Vulcan <sup>®</sup> 180 HAZ-LO <sup>®</sup> is a rechargeable, intrinsically safe, multi-function lantern featuring the latest in power LED technology and two ultra-bright blue safety taillight LEDs for rear visibility. Its large tactile push-button switch is easy to use with gloves and provides programmable access to various modes of operation. The Vulcan <sup>®</sup> 180 HAZ-LO <sup>®</sup> also features a 180-degree tilting head.
CASE MATERIAL:	Housing and face cap made from high-impact, super tough nylon offering exceptional durability. One-way valve for case venting. Available in safety yellow and safety orange with rubberized cushioned-grip handle.
DIMENSIONS:	Length: 7.43 in (18.87 cm) Width: 4.32 in (10.97 cm) Height: 4.36 in (11.07 cm)
WEIGHT:	2.45 lbs. (1111 g) with battery
LENS:	Unbreakable polycarbonate with scratch-resistant coating. Gasket-sealed.
LIGHT SOURCE:	Three (3) white high-power LEDs impervious to shock with a 50,000-hour lifetime. Two (2) ultra-bright blue taillight LEDs.
LIGHT OUTPUT:	See chart. Three (3) deep-dish parabolic reflectors produce a tight beam with optimum peripheral illumination. Optimized electronics provide regulated intensity.
ON/OFF:	Press and release for high mode, press and release again for off. Press and hold for low.
RUN TIME:	See chart. All claims to 10% of initial lumen output.
BATTERY:	Rechargeable 7.8Ahr lithium-ion battery. Fully recharges in 15 hours.
FEATURES:	IP65-rated; dust-tight and water-resistant 2-meter impact resistance tested 180-degree tilting head locks in forward facing position Battery status indicator Quick install charge rack fits same footprint as LiteBox® and Vulcan® series Large, multi-function, push-button switch easy to use with gloved hands Serialized for positive identification
MODELS:	Standard System - Vulcan® 180 quick install charging rack and both AC and DC chargers. Vehicle Mount System - Vulcan® 180 quick install charging rack and heavy-duty direct wire cord. Includes quick release buckle strap on orange model and heavy-duty strap on yellow model.
APPROVALS:	Class I, II, III, Division 1, Groups A, B, C, D, E, F, G Class I, Zone 0, Group IIC; T-Code: T4
	CE K Meets applicable United Kingdom and European Community Directives. NFPA Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position. (BC) CEC Compliant.
WARRANTY:	Streamlight's Limited Lifetime Warranty
ACCESSORIES:	100V, 120V, 230V or 240V AC (home) and 12V DC (automobile) charge cords

OUTPUT RUN TIME DISTANCE INTENSITY HIGH

400

LUMENS

10h

316m

25,000cd

LOW

130

LUMENS

24h

179m

8,000cd

