

<u>WEDGE®</u>

RECHARGEABLE EVERYDAY CARRY FLASHLIGHT

DESCRIPTION:	The Wedge [®] is a high-performance EDC light designed for clean pocket carry. It is outfitted with an intuitive rotating thumb switch providing tactile control over the constant on and THRO [®] (Temporarily Heightened Regulated Output) modes. A waterproof USB-C port in the tail offers universal and convenient charging of the integrated lithium polymer battery. A reversible pocket clip allows for concealed carry in either pocket. Made of rugged anodized aluminum, the Wedge [®] balances durability with performance.
CASE MATERIAL:	Machined aluminum alloy case. Type II MIL-Spec anodized finish. Available in Black, Coyote, Red, Blue, Purple, Orange, and Lime Green.
DIMENSIONS:	Length: 5.46 in (13.87 cm) Width: 0.60 in (1.52 cm) Height: 1.00 in (2.54 cm)
WEIGHT:	3.3 oz (93.5 g)
LENS:	Polycarbonate lens.
LIGHT SOURCE:	LED technology, impervious to shock with a 50,000-hour lifetime
LIGHT OUTPUT:	Constant On: 300 lumens; 1,200 candela; 69-meter beam distance THRO®: 1,000 lumens; 3,000 candela; 110-meter beam distance
ON/OFF:	Rotatable thumb switch - Constant on operation and momentary THRO® mode.
RUN TIME:	3 hours of run time. THRO®: Will allow 35 second bursts. All run time claims are to 10% of initial lumen output.
BATTERY:	1,500 mAh lithium polymer cell with on board safety circuit.
BATT. INDICATOR:	The indicator is located in the on/off switch. It will illuminate when the light is first turned on to display the battery level. Green will illuminate for 5 seconds to show the battery has sufficient power. Steady red indicates the battery needs to be charged soon. Blinking red indicates the battery is depleted, and shutdown is imminent.
CHARGING:	Battery fully recharges in 3 hours and charges in product. Charge indication LED: Red - Charging; Green - Charged.
FEATURES:	LED technology for extreme brightness. IPX7-rated. All openings sealed. 1-meter impact resistance tested. Removable/reversible pocket clip.
APPROVALS:	CELA Meets applicable United Kingdom and European Community Directives
WARRANTY:	Streamlight's Limited Lifetime Warranty
OPTIONAL ACCESSORIES:	USB/AC adapter(s)
	FL1 STANDARD THROT CONSTANT ON CONSTANT ON
OUTPUT	1,000 300 LUMENS LUMENS
RUN TIME	Salaria State Stat
DISTANCE	110m 69m
INTENSITY	3,000cd 1,200cd 30

All performance claims tested to ANSI/PLATO FL1-2019 Standard

HOURS