




**TLR-7® X sub****COMPACT, RAIL-MOUNTED TACTICAL LIGHT DESIGNED FOR USE WITH THE  
SIG SAUER® P365® AND SIG SAUER® P365® XL (CLOSED RAIL SYSTEMS) \*****\* DOES NOT FIT THE P365® XMACRO**

<b>DESCRIPTION:</b>	The TLR-7® X sub features multi-fuel battery capability – powered by either one (1) CR123A or one (1) Streamlight SL-B9® lithium-ion rechargeable battery pack, both delivering 500 lumens and 5,000 candela. The integrated rail clamp is designed to rapidly attach/detach from the side of the weapon, providing smooth installation and removal without having to put your hands in front of the muzzle. Features a specialized clamp system for mounting on SIG SAUER® P365®/XL accessory rails. Please refer to <a href="http://streamlight.com">streamlight.com</a> for the current compatibility list.
<b>CASE MATERIAL:</b>	Body and face cap: 6000 Series machined aircraft aluminum with black anodized finish. Switch housing: Impact- and chemical-resistant engineered polymer.
<b>DIMENSIONS:</b>	Width: 1.16 in (2.95 cm)      Height: 1.24 in (3.15 cm)      Length: 2.51 in (6.38 cm)
<b>WEIGHT:</b>	<b>CR123A:</b> 2.39 oz (67.8 g) with battery. <b>SL-B9®:</b> 2.64 oz (74.8 g) with battery.
<b>LENS:</b>	High temperature, shock-mounted, impact-resistant, scratch-resistant BOROFLOAT® glass.
<b>LIGHT SOURCE:</b>	White LED, impervious to shock with a 50,000-hour lifetime.
<b>LIGHT OUTPUT:</b>	500 lumens, 5,000 candela peak beam intensity, and 141m beam distance. Custom TIR optic produces a concentrated beam with optimum peripheral illumination. Optimized electronics provide regulated intensity.
<b>ON/OFF:</b>	Rear switches left and right of trigger guard provide ambidextrous operation. Momentary and constant on operation. User-activated strobe.
<b>RUN TIME:</b>	<b>CR123A:</b> 1.5 hours of continuous operation to the 10% output level. <b>SL-B9®:</b> 1 hour of continuous operation to the 10% output level.
<b>BATTERY:</b>	<b>CR123A:</b> One (1) 3-volt CR123A lithium battery with a storage life of 10 years. <b>SL-B9®:</b> One (1) Streamlight Li-Ion 850mAh USB-C rechargeable battery pack with integrated safety circuit, rechargeable up to 500 cycles. Battery installed/removed through face cap. No need to remove from firearm. Charges within 2.5 hours via USB-C cord or optional bank charger.
<b>FEATURES:</b>	Multi-fuel operation; SL-B9® Li-Ion rechargeable battery pack or CR123A. High-power LED for extreme brightness. Ambidextrous operation. One-handed snap on and tighten interface keeps hands away from muzzle when attaching or detaching. Extensively live fire tested. Operating temperature: -40°F to +120°F (CR123A) or -4°F to +120°F (SL-B9®). IPX7-rated design; waterproof to 1 meter for 30 minutes. Serialized for positive identification.
<b>APPROVALS:</b>	 Meets applicable United Kingdom and European Community Directives  CEC Compliant (with SL-B9® only)  TAA Compliant
<b>WARRANTY:</b>	Streamlight's Limited Lifetime Warranty
<b>OPTIONAL ACCESSORIES:</b>	SL-B9® Li-Ion Battery Bank Charger

All Rights Reserved. SIG SAUER® and P365® are registered trademarks of SIG Sauer, Inc. Streamlight has not sought endorsement of this product from SIG Sauer, Inc.

BOROFLOAT® is a registered trademark of SCHOTT AG.