

**TLR-7® X sub****COMPACT, RAIL-MOUNTED TACTICAL LIGHT DESIGNED FOR USE WITH  
1913 RAILED SUBCOMPACT HANDGUNS**

<b>DESCRIPTION:</b>	The TLR-7® X sub features multi-fuel battery capability – powered by either one (1) CR123A or one (1) Streamlight SL-B9® lithium-ion rechargeable battery pack, both delivering 500 lumens and 5,000 candela. The integrated rail clamp is designed to rapidly attach/detach from the side of the weapon, providing smooth installation and removal without having to put your hands in front of the muzzle. The specialized clamp system allows for mounting on 1913 railed subcompact handguns including: the Smith & Wesson® M&P® M2.0® subcompact, Beretta® Px4 Storm subcompact, Springfield Armory® XD-E™, XD-S® and Hellcat® Pro, Heckler & Koch® HK45 compact, and SIG SAUER® P365® XMACRO. Please refer to <a href="http://streamlight.com">streamlight.com</a> for the current compatibility list.
<b>CASE MATERIAL:</b>	Body and face cap: 6000 Series machined aircraft aluminum with black anodized finish. Switch housing: Impact- and chemical-resistant engineered polymer.
<b>DIMENSIONS:</b>	Width: 1.16 in (2.95 cm)      Height: 1.24 in (3.15 cm)      Length: 2.51 in (6.38 cm)
<b>WEIGHT:</b>	<b>CR123A:</b> 2.39 oz (67.8 g) with battery. <b>SL-B9®:</b> 2.64 oz (74.8 g) with battery.
<b>LENS:</b>	High temperature, shock-mounted, impact-resistant, scratch-resistant BOROFLOAT® glass.
<b>LIGHT SOURCE:</b>	White LED, impervious to shock with a 50,000-hour lifetime.
<b>LIGHT OUTPUT:</b>	500 lumens, 5,000 candela peak beam intensity, and 141m beam distance. Custom TIR optic produces a concentrated beam with optimum peripheral illumination. Optimized electronics provide regulated intensity.
<b>ON/OFF:</b>	Rear switches left and right of trigger guard provide ambidextrous operation. Momentary and constant on operation. User-activated strobe.
<b>RUN TIME:</b>	<b>CR123A:</b> 1.5 hours of continuous operation to the 10% output level. <b>SL-B9®:</b> 1 hour of continuous operation to the 10% output level.
<b>BATTERY:</b>	<b>CR123A:</b> One (1) 3-volt CR123A lithium battery with a storage life of 10 years. <b>SL-B9®:</b> One (1) Streamlight Li-Ion 850mAh USB-C rechargeable battery pack with integrated safety circuit, rechargeable up to 500 cycles. Battery installed/removed through face cap. No need to remove from firearm. Charges within 2.5 hours via USB-C cord or optional bank charger.
<b>FEATURES:</b>	Multi-fuel operation; SL-B9® Li-Ion rechargeable battery pack or CR123A. High-power LED for extreme brightness. Ambidextrous operation. One-handed snap on and tighten interface keeps hands away from muzzle when attaching or detaching. Securely fits a broad range of weapons using key kit provided. Extensively live fire tested. Operating temperature: -40°F to +120°F (CR123A) or -4°F to +120°F (SL-B9®). IPX7-rated design; waterproof to 1 meter for 30 minutes. Serialized for positive identification.
<b>APPROVALS:</b>	 Meets applicable United Kingdom and European Community Directives  CEC Compliant (with SL-B9® only)  TAA Compliant
<b>WARRANTY:</b>	Streamlight's Limited Lifetime Warranty
<b>OPTIONAL ACCESSORIES:</b>	SL-B9® Li-Ion Battery Bank Charger

All Rights Reserved. Smith & Wesson®, M&P®, and M2.0® are registered trademarks of Smith & Wesson Inc. Beretta® is a registered trademark of Fabbrica D'Armi P. Beretta, S.p.A. Springfield Armory®, XD-E™, XD-S®, and Hellcat® are trademarks or registered trademarks of Springfield, Inc. Heckler & Koch® is a registered trademark of Heckler & Koch GmbH. SIG SAUER® and P365® are registered trademarks of SIG Sauer, Inc. Streamlight has not sought endorsement from any of the Companies mentioned in this paragraph.

BOROFLOAT® is a registered trademark of SCHOTT AG.