



TLR-7® X CONTOUR REMOTE
MULTI-FUEL, RAIL-MOUNTED TACTICAL LIGHT WITH GRIP SWITCH

- DESCRIPTION:** The TLR-7® X Contour Remote weapon-mounted light features multi-fuel capability - powered by either one (1) CR123A or one (1) Streamlight SL-B9™ lithium-ion rechargeable battery. The light includes customizable rear paddle switches, as well as a contoured remote switch that activates naturally when using a firing grip. This unit has two models available for GLOCK® (fits most railed Gen 4/Gen 5 handguns) or SIG SAUER® (fits P320® XCarry frame).
- CASE MATERIAL:** Body and face cap: 6000 Series machined aircraft aluminum with black anodized finish
Switch housing: Impact- and chemical-resistant engineered polymer
- DIMENSIONS:** Width: 1.16 in (2.95 cm) Height: 1.79 in (4.55 cm) Length: 4.6 in (11.68 cm)
- WEIGHT:** CR123A: 2.69 oz (76.3 g) with battery.
SL-B9: 2.85 oz (80.7g) with battery.
- LENS:** High-temperature, shock-mounted, impact-resistant BOROFLOAT® glass
- LIGHT SOURCE:** White LED, impervious to shock with a 50,000-hour lifetime
- LIGHT OUTPUT:** 500 lumens; 5,000 candela peak beam intensity; 140m beam distance
Custom TIR optic produces a concentrated beam with optimum peripheral illumination
Optimized electronics provide regulated intensity
- ON/OFF:** Rear switches left and right of trigger guard provide ambidextrous operation.
Momentary and constant on operation.
User-activated strobe.
- RUN TIME:** CR123A: 1.5 continuous hours to the 10% output level
SL-B9: 1 hour continuous operation to the 10% output level
- BATTERY:** CR123A: One (1) 3-volt lithium battery with a storage life of 10 years
SL-B9: One (1) Streamlight Li-Ion 850mAh USB-C rechargeable battery pack with integrated safety circuit, rechargeable up to 500 cycles. Charges within 2.5 hours via USB-C cord or optional bank charger.
- FEATURES:** High-power LED for extreme brightness
Ambidextrous operation
One-handed snap-on and tighten interface keeps hands away from muzzle when installing
Securely fits select GLOCK® and SIG SAUER® handguns
Extensively live fire tested
Operating temperature: -40°F to +120°F
IPX7-rated design; waterproof to 1 meter for 30 minutes
Serialized for positive identification
- APPROVALS:** CE UK Meets applicable United Kingdom and European Community Directives
BC CEC Compliant
- WARRANTY:** Streamlight's Limited Lifetime Warranty
- OPTIONAL ACCESSORIES:** Mounting adapters, HPL face cap, SL-B9 Bank Charger

All rights reserved. GLOCK® and SIG SAUER® are registered trademarks of Glock, Inc. and SIG Sauer, Inc., respectively. Streamlight has not sought endorsement of this product from Glock, Inc. or SIG Sauer, Inc.

BOROFLOAT® is a registered trademark of SCHOTT AG.

Issued: 12/03/2020

Revised: 01/11/2024 Rev: 2

Assembled in the USA.

Document #366