



TLR-7® X sub**COMPACT, RAIL-MOUNTED TACTICAL LIGHT DESIGNED FOR USE WITH 1913 SHORT RAILED SUBCOMPACT HANDGUNS**

DESCRIPTION:	The TLR-7® X sub features multi-fuel battery capability – powered by either one (1) CR123A or one (1) Streamlight SL-B9® lithium-ion rechargeable battery pack, both delivering 500 lumens and 5,000 candela. The integrated rail clamp is designed to rapidly attach/detach from the side of the weapon, providing smooth installation and removal without having to put your hands in front of the muzzle. Features a specialized clamp system for mounting on the Springfield Armory® Hellcat® and Heckler & Koch® CC9 accessory rail. Please refer to streamlight.com for the current compatibility list.
CASE MATERIAL:	Body and face cap: 6000 Series machined aircraft aluminum with black anodized finish. Switch housing: Impact- and chemical-resistant engineered polymer.
DIMENSIONS:	Width: 1.16 in (2.95 cm) Height: 1.24 in (3.15 cm) Length: 2.51 in (6.38 cm)
WEIGHT:	CR123A: 2.39 oz (67.8 g) with battery. SL-B9®: 2.64 oz (74.8 g) with battery.
LENS:	High temperature, shock-mounted, impact-resistant, scratch-resistant BOROFloat® glass.
LIGHT SOURCE:	White LED, impervious to shock with a 50,000-hour lifetime.
LIGHT OUTPUT:	500 lumens, 5,000 candela peak beam intensity, and 141m beam distance. Custom TIR optic produces a concentrated beam with optimum peripheral illumination. Optimized electronics provide regulated intensity.
ON/OFF:	Rear switches left and right of trigger guard provide ambidextrous operation. Momentary and constant on operation. User-activated strobe.
RUN TIME:	CR123A: 1.5 hours of continuous operation to the 10% output level. SL-B9®: 1 hour of continuous operation to the 10% output level.
BATTERY:	CR123A: One (1) 3-volt CR123A lithium battery with a storage life of 10 years. SL-B9®: One (1) Streamlight Li-Ion 850mAh USB-C rechargeable battery pack with integrated safety circuit, rechargeable up to 500 cycles. Battery installed/removed through face cap. No need to remove from firearm. Charges within 2.5 hours via USB-C cord or optional bank charger.
FEATURES:	Multi-fuel operation; SL-B9® Li-Ion rechargeable battery pack or CR123A. High-power LED for extreme brightness. Ambidextrous operation. One-handed snap on and tighten interface keeps hands away from muzzle when attaching or detaching. Extensively live fire tested. Operating temperature: -40°F to +120°F (CR123A) or -4°F to +120°F (SL-B9®). IPX7-rated design; waterproof to 1 meter for 30 minutes. Serialized for positive identification.
APPROVALS:	  Meets applicable United Kingdom and European Community Directives  CEC Compliant (with SL-B9® only) TAA TAA Compliant
WARRANTY:	Streamlight's Limited Lifetime Warranty
OPTIONAL ACCESSORIES:	SL-B9® Li-Ion Battery Bank Charger

All Rights Reserved. Springfield Armory® and Hellcat® are registered trademarks of Springfield, Inc. Heckler & Koch® is a registered trademark of Heckler & Koch GmbH. Streamlight has not sought endorsement of this product from Springfield, Inc.

BOROFloat® is a registered trademark of SCHOTT AG.