






PROTAC® 2.0 RAIL MOUNT

- DESCRIPTION:** The ProTac® 2.0 Rail Mount is a 2,000-lumen tactical weapon-mounted flashlight that uses a proprietary Streamlight SL-B50® protected Li-Ion rechargeable battery pack. It features a tactical tail cap switch for momentary or constant on operation and three different user-selectable programs. A remote pressure switch option is also available. The SL-B50® charges directly via USB-C port in the body of the battery pack. The battery is keyed to ensure proper alignment of the charging port. USB-C cord included.
- CASE MATERIAL:** 6000 series machined aircraft aluminum with Type II MIL-Spec anodized finish. Available in black.
- DIMENSIONS:** Length: 6.30 in (16 cm) Head Diameter: 1.46 in (3.7 cm) Body Diameter: 1.02 in (2.6 cm)
- WEIGHT:** 9.06 oz (257 g) with (1) Streamlight SL-B50® protected Li-Ion USB-rechargeable battery pack (included in purchase).
- LENS:** Glass with anti-reflective coating; gasket-sealed
- LIGHT SOURCE:** LED technology, impervious to shock with a 50,000-hour lifetime
- LIGHT OUTPUT:** High: 2,000 lumens, 17,700 candela peak beam intensity, 266 m beam distance.
Low: 250 lumens, 2,150 candela peak beam intensity, 93 m beam distance.
Fully regulated output for consistent lumen performance over the entire battery life.
- ON/OFF:** Multi-function, push-button tail switch with momentary and latching constant on operations. Optional remote switch available in momentary only and momentary/latching versions. One-handed operation of momentary, variable intensity, or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe (factory default), high only, or low/high.
- RUN TIME:** High: 2.5 hours; Low: 11 hours; Strobe: 4.5 hours
All run time claims are to 10% of initial output.
- BATTERY:** (1) Streamlight SL-B50® protected Li-Ion USB-rechargeable battery pack with on-board safety control, 4,900mAh. Recharges in 6 hours.
- FEATURES:** LED technology for extreme brightness.
IP67-rated; dust-tight and waterproof to 1 meter for 30 minutes.
All openings O-ring sealed.
2-meter impact resistance tested.
Securely fits a broad range of weapons.
Mounts directly to guns with MIL-STD-1913 (Picatinny) rails or M-LOK® and M-LOK® compatible rail systems.
Extensively live fire tested, impact-resistant construction.
Serialized for positive identification.
- APPROVALS:**   Meets applicable United Kingdom and European Community Directives
 CEC Compliant
- WARRANTY:** Streamlight's Limited Lifetime Warranty
- OPTIONAL ACCESSORIES:** USB-C charge cord, remote pressure switch, SL-B50® battery pack