

SURVIVOR PIVOT® ATEX

DESCRIPTION: The Survivor Pivot® ATEX is an intrinsically safe, Zone 0 rated flashlight that features a dual beam and a 90-degree articulating head. Its spot beam uses a cool white, high-power LED for maximum distance illumination and its flood beam is angled downward for area illumination. The large translucent push-button switch with battery status indicator provides easy access to microprocessor-controlled intensity modes, even with gloved hands. Heavy-duty clip securely attaches to gear for hands-free use. Optional removable magnet with 30 lb. pull strength features a replaceable rubber boot.

CASE MATERIAL: Housing, base, and battery housing made from high-impact, super tough polymer offering exceptional durability. Spring-loaded clip with built-in D-ring easily attaches to belts and harnesses and reduces unwanted rotation. One-way valve for case venting.

DIMENSIONS: Height: 7.93 in (20.14 cm); Width: 2.86 in (7.26 cm)
Thickness: 3.29 in (8.36 cm); Thickness (w/magnet): 3.64 in (9.25 cm)

WEIGHT: Non-Magnet Li-Ion: 16.2 oz (459 g) Alkaline: 16.7 oz (473 g)
Magnet Li-Ion: 17.6 oz (499 g) Alkaline: 18.1 oz (513 g)

LENS: Unbreakable polycarbonate with silicone anti-scratch coating assembled in a heavy-duty bezel. O-ring sealed.

LIGHT OUTPUT: See charts below. Optimized electronics provide regulated intensity.
Spot: Custom "Total Internal Reflection" (TIR) optic for narrow beam and optimum peripheral illumination
Flood: Unique bias reflector provides maximum area illumination



ON/OFF: Ultrasonic welded switch designed for extremely long life. Translucent rubber dome push-button actuator provides easy operation, even when wearing heavy gloves.


RUN TIME: See charts below. All claims to 10% of initial lumen output.

BATTERY: - 2.6 Ahr Li-Ion battery pack rechargeable up to 1,000 times available with 100/230/240VAC systems. Fully charges in 5 hours. Battery status indicator shows red when charging; turns green when fully charged.
- Three (3) optional AA alkaline batteries

BATTERY STATUS INDICATOR: The translucent switch boot contains an integrated red/green battery status indicator.
- Solid green for 5 seconds: Light is charged and ready for use
- Solid red: 45 minutes or less of battery life remaining
- Flashing red: 15 minutes or less of battery life remaining

FEATURES: Simultaneous spot and flood mode for maximum illumination
Translucent switch boot with integrated battery status indicator
Charge cradle designed for one-handed light removal
Multi-fuel design; accepts multiple battery types
IP67-rated; dust-tight and waterproof to 1 meter for 30 minutes
2-meter impact resistance tested
Serialized for positive identification



APPROVALS:**  SGSNA24ATEX012901; IECEx SNA 24.0001
II 1G Ex ia op is IIC T3/T4 Ga

** See product for specific ratings.

T-CLASS T4: Duracell MN1500, Varta 4006, Energizer EN91
T-CLASS T3: Streamlight pack 90340



NFPA Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018).
Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position.

CE Meets applicable European Community Directives

WARRANTY: Streamlight's Limited Lifetime Warranty

ACCESSORIES: 5-Unit Bank Charger

Rechargeable Li-Ion Battery

	FL1 STANDARD	COMBO	SPOT	FLOOD		
	FL1 STANDARD	HIGH	LOW	HIGH	LOW	HIGH
OUTPUT		325 LUMENS	80 LUMENS	300 LUMENS	70 LUMENS	300 LUMENS
RUN TIME		3.75h	13h	4.25h	16h	4.25h
DISTANCE		276m	141m	369m	184m	35m
INTENSITY		19,000cd	5,000cd	34,000cd	8,500cd	300cd

AA Alkaline Batteries

	FL1 STANDARD	COMBO	SPOT	FLOOD		
	FL1 STANDARD	HIGH	LOW	HIGH	LOW	HIGH
OUTPUT		325 LUMENS	80 LUMENS	300 LUMENS	70 LUMENS	300 LUMENS
RUN TIME		4.5h	12h	5.5h	15h	5.5h
DISTANCE		276m	141m	369m	184m	35m
INTENSITY		19,000cd	5,000cd	34,000cd	8,500cd	300cd

All performance claims tested to ANSI/PLATO FL1-2019 Standard

Issued: 04/16/2024

Revised: 04/25/2024

Rev: 1

Engineered in the USA, Made in China.

Document #397