





**TLR-7® HL-X sub USB****MULTI-FUEL, HIGH-LUMEN, RAIL-MOUNTED LIGHT DESIGNED FOR USE WITH  
1913 SHORT RAILED SUBCOMPACT HANDGUNS**

<b>DESCRIPTION:</b>	The TLR-7® HL-X sub USB features 1,000 lumens and 10,000 candela when powered by one (1) Streamlight SL-B9® proprietary lithium-ion rechargeable battery pack. Multi-fuel capability allows for operation with one (1) CR123A battery delivering 500 lumens and 5,000 candela. The specialized clamp system allows for mounting on 1913 short railed subcompact handguns including: the Smith & Wesson® M&P® M2.0® subcompact, Beretta® Px4 Storm subcompact, Springfield Armory® XD-E™, XD-S® and Hellcat® Pro, Heckler & Koch® HK45 compact, and SIG SAUER® P365® XMACRO. Please refer to <a href="http://streamlight.com">streamlight.com</a> for the current compatibility list.
<b>CASE MATERIAL:</b>	Body and face cap: 6000 Series machined aircraft aluminum with black anodized finish. Switch housing: Impact- and chemical-resistant engineered polymer.
<b>DIMENSIONS:</b>	Width: 1.16 in (2.95 cm)      Height: 1.24 in (3.15 cm)      Length: 2.51 in (6.38 cm)
<b>WEIGHT:</b>	SL-B9®: 2.49 oz (70.6 g) with battery CR123A: 2.39 oz (67.8 g) with battery
<b>LENS:</b>	High temperature, shock-mounted, impact-resistant BOROFLOAT® glass.
<b>LIGHT SOURCE:</b>	White LED, impervious to shock with a 50,000-hour lifetime.
<b>LIGHT OUTPUT:</b>	SL-B9®: 1,000 lumens, 10,000 candela peak beam intensity, and 200m beam distance (default) or programmable to 500 lumens, 5,000 candela peak beam intensity, and 141m beam distance. CR123A: 500 lumens, 5,000 candela peak beam intensity, and 141m beam distance. Optimized electronics provide regulated intensity.
<b>ON/OFF:</b>	Rear switches left and right of trigger guard provide ambidextrous operation. Momentary and constant on operation. User-programmable strobe.
<b>RUN TIME:</b>	SL-B9®: 30 minutes (default) or 1 hour (programmable) continuous operation to 10% output level. CR123A: 1.5 hours continuous operation to 10% output level.
<b>BATTERY:</b>	SL-B9®: One (1) Streamlight Li-Ion 850mAh USB-C rechargeable battery with integrated safety circuit, rechargeable up to 500 cycles. Charges within 2.5 hours via USB-C cord or bank charger. CR123A: One (1) 3-volt CR123A lithium battery with a storage life of 10 years.
<b>FEATURES:</b>	High-lumen operation with SL-B9® Li-Ion rechargeable battery pack. Multi-fuel operation; SL-B9® Li-Ion rechargeable battery pack or CR123A. Ambidextrous operation. Securely fits various subcompact weapons using the key kit provided. Extensively live fire tested. Operating temperature: -4°F to +120°F (SL-B9®) or -40°F to +120°F (CR123A). IPX7-rated design; waterproof to 1 meter for 30 minutes. Serialized for positive identification.
<b>APPROVALS:</b>	  Meets applicable United Kingdom and European Community Directives  CEC Compliant (with SL-B9® only)  TAA Compliant
<b>WARRANTY:</b>	Streamlight's Limited Lifetime Warranty
<b>OPTIONAL ACCESSORIES:</b>	SL-B9® Li-Ion Battery Bank Charger

All rights reserved. Smith & Wesson®, M&P®, and M2.0® are registered trademarks of Smith & Wesson Inc. Beretta® is a registered trademark of Fabbrica D'Armi P. Beretta, S.p.A. Springfield Armory®, XD-E™, XD-S®, and Hellcat® are trademarks or registered trademarks of Springfield, Inc. Heckler & Koch® is a registered trademark of Heckler & Koch GmbH. SIG SAUER® and P365® are registered trademarks of SIG Sauer, Inc. Streamlight has not sought endorsement from any of the Companies mentioned in this paragraph.

BOROFLOAT® is a registered trademark of SCHOTT AG.