STREMLIGHT:

PRODUCT FACT SHEET

SL-B9® LI-ION BATTERY BANK CHARGER

DESCRIPTION: The Streamlight SL-B9® Li-Ion battery bank charger is designed to individually charge

and maintain the charge of up to eight (8) Streamlight SL-B9® Li-Ion rechargeable battery packs. Integrated LED charge indicators provide a visual battery status at each battery location. The bank charger is available with or without eight (8) SL-B9®

Li-Ion rechargeable battery packs.

CASE MATERIAL: Impact-resistant engineered polymer housing.

DIMENSIONS: Length: 10.5 in (26.7 cm)

Width: 3.2 in (8.1 cm) Heigh

Height: 1.0 in (2.5 cm)

WEIGHT:

5.8 oz (164 g) without batteries

11.4 oz (323 g) with eight (8) SL-B9® batteries

BATTERY:

Streamlight SL-B9® Li-Ion rechargeable battery pack with on-board safety protection

and USB-C charge port, rechargeable up to 300 times.

CHARGE INPUT: 120V AC or international power supply wall adapter or 12V DC direct wire with 2.5mm

barrel plug are available to connect with the charger.

CHARGE TIME: 2.5 hours maximum to charge one battery pack or multiple battery packs.

LED charge indicator for quick visual of charge status:

Red = Charging, Green = Charged.

FEATURES: Charges up to eight (8) SL-B9[®] Li-lon rechargeable battery packs.

Charger temperature safety circuit prevents damage to batteries while charging.

WARRANTY: Streamlight's Limited Lifetime Warranty

APPROVALS: CE LA Meets applicable European Community and United Kingdom Directives.

(BC) CEC Compliant

NFPA Meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in upright position.

OPTIONAL

ACCESSORIES: N/A

Issued: 06/13/2024

Revised: Rev: Assembled in the USA, Document #409