

PRODUCT FACT SHEET

PROTAC® 2AA-X USB

MULTI-FUEL, PERSONAL CARRY TACTICAL FLASHLIGHT

Producing 550 lumens and 10,250 candela, the ProTac® 2AA-X USB flashlight uses Streamlight's **DESCRIPTION:**

proprietary protected lithium polymer USB-C rechargeable battery pack. It also accepts two (2) AA disposable batteries creating 270 lumens and 5,000 candela. This light features a tail cap switch for

momentary or constant on operation and three different user-selectable programs.

6000 series machined aircraft aluminum with anodized finish. Available in black or coyote. **CASE MATERIAL:**

DIMENSIONS: Length: 6 in (15.3 cm) Head diameter: 0.9 in (2.3 cm) Body Diameter: 0.7 in (1.8 cm)

3.5 oz (99 g) with either battery type. WEIGHT:

Glass lens. Gasket-sealed. LENS:

LED technology, impervious to shock with a 50,000-hour lifetime. LIGHT SOURCE:

LIGHT OUTPUT: See chart. Optimized electronics provides regulated intensity.

Multi-function, push-button tail switch. One-handed operation of momentary, variable intensity, or ON/OFF:

strobe modes. TEN-TAP® programmable switch allows for user selection of one of three different

programs: high/strobe/low (factory default), high only, or low/high.

See chart for specific battery type. All claims are to 10% of initial lumen output. **RUN TIME:**

One (1) Streamlight proprietary protected lithium polymer USB-C rechargeable battery pack with **BATTERY:**

on-board safety control, 1600mAh, rechargeable up to 500 times. Recharges in 4 hours.

Also accepts two (2) AA alkaline batteries.

FEATURES: LED technology for extreme brightness.

IPX7-rated design; waterproof to 1 meter. 2-meter impact resistance tested.

Multi fuel; accepts proprietary lithium polymer or AA batteries.

TEN-TAP® programmable switch allows user to select one of three different programs.

Anti-roll face cap.

Serialized for positive identification. Removable pocket clip and holster.

Streamlight's Limited Lifetime Warranty **WARRANTY:**

CE LA Meets applicable United Kingdom and European Community Directives. APPROVALS:

(BC) CEC Compliant (with rechargeable battery pack only).

OPTIONAL

Holster, charge cord **ACCESSORIES:**

OUTPUT

RUN TIME

DISTANCE

INTENSITY

Lithium Polymer Battery

FL 1 Standard	HIGH	LOW
M	550	40
7 }	LUMENS	LUMENS
0	2h 15min	16h
	203m	54m
	10,250cd	740cd

Strobe Run Time: 4 hrs. 30 min

AA Batteries

FL 1 Standard	HIGH	LOW
M	270	18
7 %	LUMENS	LUMENS
0	2h 30min	48h
	141m	40m
	5,000cd	400cd

Strobe Run Time: 5 hrs.

All performance claims tested to ANSI/PLATO FL1-2019 Standard

Issued: 05/07/2024

Revised: Rev: 0