

PRODUCT FACT SHEET

PROTAC HL® 6 RECHARGEABLE LI-ION FLASHLIGHT

The ProTac HL® 6 is a 5,300-lumen flashlight powered by two proprietary Streamlight SL-B48® protected **DESCRIPTION:**

Li-Ion USB rechargeable battery packs. The ProTac HL® 6 rechargeable system comes with a charge cord and two SL-B48® rechargeable battery packs that feature an integrated USB-C charge port. The ProTac HL® 6 offers the latest in power LED technology and three different user-selectable programs. The

textured rubber sleeve and included lanyard ensure you'll never lose your grip.

CASE MATERIAL: 6000 series machined aircraft aluminum with anodized finish. Available in black.

DIMENSIONS: Length: 10.5 in (26.6 cm) Head Diameter: 2.35 in (6.0 cm) Barrel Diameter: 1.25 in (3.2 cm)

WEIGHT: 1.3 lbs. (590 g) with two Streamlight SL-B48® protected Li-Ion USB rechargeable battery packs (included

in purchase)

LENS: Glass lens with anti-reflective coating. Gasket-sealed.

LIGHT SOURCE: LED technology, impervious to shock with a 50,000-hour lifetime. Total internal reflection optic.

LIGHT OUTPUT: See chart. Optimized electronics provides thermal management and regulated intensity.

ON/OFF: Multi-function, easy access, head-mounted, push-button switch. One-handed operation of momentary,

variable intensity, or strobe mode. TEN-TAP® programmable switch allows for user selection of one of

three different programs: high/strobe/low (factory default), high only, or low/medium/high.

RUN TIME: See chart. All claims to 10% of initial lumen output.

Two (2) Streamlight SL-B48® protected Li-Ion USB rechargeable battery packs with on-board safety **BATTERY:**

control, 5000mAh, rechargeable up to 500 times. Each battery pack recharges in 5 hours.

FEATURES: Cool white LED technology for extreme brightness.

IPX7-rated design; waterproof to 1 meter for 30 minutes.

1-meter impact resistance tested.

LED Solid State Power Regulation provides maximum light output throughout battery life.

TEN-TAP® programmable switch allows user to select one of three different programs.

Anti-roll face cap. Sure grip rubber sleeve.

Serialized for positive identification.

WARRANTY: Streamlight's Limited Lifetime Warranty

CE Keets applicable United Kingdom and European Community Directives **APPROVALS:**

(BC) CEC Compliant

OPTIONAL

ACCESSORIES: Holster, lanyard, charge cord

	FL 1 Standard	HIGH	MEDIUM	LOW
OUTDUT	M	5300	1500	450
OUTPUT	4 F	LUMENS	LUMENS	LUMENS
RUN TIME	0	2h	3h 45min	12h 30min
DISTANCE		566m	303m	164m
INTENSITY		80,000cd	23,000cd	6,700cd

Strobe Run Time: 4 hours

All performance claims tested to ANSI/PLATO FL1-2019 Standard

Issued: 04/11/2024