

PRODUCT FACT SHEET

MEGASTREAM® USB

LITHIUM-ION RECHARGEABLE FLASHLIGHT

DESCRIPTION: The MegaStream® USB is powered by (1) Streamlight SL-B34® lithium-ion rechargeable battery pack

delivering 1,800 lumens and 26,000 candela. It features a tail cap switch, momentary or constant on operation, high/medium/low beams, a pocket clip for convenience, and amazing brightness and run time for a light of its size. The anodized aluminum housing makes the light extremely durable and abrasion resistant. To charge the light, slide the head cover back to expose the USB-C port.

CASE MATERIAL: Machined aluminum alloy case. Type II MIL-Spec anodized finish. Available in Black.

DIMENSIONS: Length: 5.3 in (13.4 cm) Body Diameter: 1.1 in (2.8 cm)

WEIGHT: 5.4 oz (152 g) with battery (included with purchase).

LENS: Unbreakable polycarbonate lens.

LIGHT SOURCE: LED technology, impervious to shock with a 30,000-hour lifetime.

LIGHT OUTPUT: High: 1,800 lumens, 26,000 candela peak beam intensity, 322 m beam distance. Med: 500 lumens, 7,200 candela peak beam intensity, 170m beam distance.

Low: 150 lumens, 2,100 candela peak beam intensity, 92m beam distance.

ON/OFF: Push-button tail switch with momentary or constant on operation.

RUN TIME: High: 2 hours; Medium: 3.5 hours; Low: 13 hours All run time claims are to 10% of initial lumen output.

BATTERY: (1) 3,500mAh Streamlight SL-B34® lithium-ion cell with on-board safety circuit.

Fully recharges in 5 hours and charges battery in product. Charge indication LED: Red - Charging; Green - Charged.

FEATURES: LED technology for extreme brightness.

IPX7-rated design; waterproof to 1 meter for 30 minutes. All openings O-ring sealed.

Self-keying battery ensures proper alignment of the charging port.

2-meter impact resistance tested.

Removable pocket clip. USB-C cord included.

APPROVALS: CE K Meets applicable United Kingdom and European Community Directives

(BC) CEC Compliant

WARRANTY: Streamlight's Limited Lifetime Warranty

OPTIONAL

ACCESSORIES: USB/AC adapter(s)

FL1 STANDARD	HIGH	MEDIUM	Low
314	1,800 LUMENS	500 LUMENS	150 LUMENS
(1)	2h	3.5h	13h
	322 m	170 m	92m
	26,000 cd	7,200 cd	2,100 cd

All performance claims tested to ANSI/PLATO FL1-2019 Standard

INTENSITY

OUTPUT

RUN TIME

DISTANCE

Issued: 11/20/2024