




PROTAC® RAIL MOUNT HP-X PRO
MULTI-FUEL, HIGH CANDELA LONG GUN LIGHT

DESCRIPTION:	Gun-mounted tactical light featuring 105,000 candela and extreme beam reach to penetrate smoke, fog, and photonic barriers. Its Jack-Cap® tail cap switch offers operational switch redundancy – push-button operation or remote pressure switch operation. The rail clamp is designed to securely attach to rifles, carbines, and submachine guns with a MIL-STD-1913 rail or with the included M-LOK® mount, allowing for alternative mounting options to M-LOK® and M-LOK® compatible rail systems. The light is powered by (2) CR123A lithium batteries or (1) Streamlight rechargeable SL-B26® battery pack.
CASE MATERIAL:	6000 Series machined aircraft aluminum with black anodized finish
DIMENSIONS:	Length: 5.63 in (14.3 cm) Head Diameter: 1.38 in (3.5 cm) Height: 1.72 in (4.4 cm)
WEIGHT:	6.4 oz (181 g) with (2) CR123A batteries. 7.0 oz (198 g) with (1) SL-B26® rechargeable battery pack.
LENS:	High-temperature, shock-mounted, AR coated, impact-resistant BOROFLOAT® glass.
LIGHT SOURCE:	White LED impervious to shock with a 50,000-hour lifetime.
LIGHT OUTPUT:	High: 800 lumens; 105,000 candela peak beam intensity; 648m beam distance Low: 55 lumens; 7,600 candela peak beam intensity; 174m beam distance Solid state current regulation for consistent illumination level and the reflector produces a concentrated beam with optimum peripheral illumination.
ON/OFF:	Multi-function, push-button tail switch with momentary and latching constant on operations. Optional remote switch available in momentary only and momentary/latching versions. One-handed operation of momentary, variable intensity, or strobe mode. TEN-TAP® programmable switch allows the user to select one of three different programs: high/strobe (factory default), high only, or low/high.
RUN TIME:	SL-B26: High: 2 hours Low: 26 hours Strobe: 3.5 hours CR123A: High: 1.5 hours Low: 18 hours Strobe: 2.5 hours
BATTERY:	(2) 3-volt CR123A lithium batteries with a storage life of 10 years. Also accepts (1) Streamlight SL-B26® lithium-ion rechargeable battery pack.
FEATURES:	105,000 candela output provides visibility through smoke, fog with 648m beam distance Jack-Cap® tail cap offers push-button switch and port for a remote pressure switch One-handed snap-on and tighten interface keeps hands away from muzzle when attaching/detaching from the firearm Mounts directly to guns with MIL-STD-1913 (Picatinny) rails or M-LOK® and M-LOK® compatible rails Extensively live fire tested, impact-resistant construction IPX7-rated with standard push-button switch installed; waterproof to 1 meter for 30 minutes IPX4-rated with the remote pressure switch installed for water-resistant operation
APPROVALS:	  Meets applicable United Kingdom and European Community Directives  CEC Compliant (USB models only)
WARRANTY:	Streamlight's Limited Lifetime Warranty
OPTIONAL ACCESSORIES:	Battery charge cradles, replacement batteries, remote pressure switches