



# DUALIE® 3AA COLOR-RITE®

INTRINSICALLY SAFE FLASHLIGHT WITH COLOR-RITE TECHNOLOGY®



The Dualie design produces either a spot beam with a cool white LED or a flood beam that uses a CRI LED



Available Colors: 

The intrinsically safe, Dualie 3AA Color-Rite provides the option of bright, white light to see what's ahead of you or high CRI light with Streamlight's Color-Rite Technology® for true color recognition.

### KEY FEATURES

- Intrinsically safe
- Features one cool white LED and a 90 CRI LED
- Dual head switches for easy beam selection and one-handed operation

### OUTPUT

	SPOT (COOL WHITE)	FLOOD (WARM WHITE)	COMBO
LUMENS	225	175	320
CANDELA	8,000	380	7,000
DISTANCE	179m	39m	167m
RUN TIME	8 hrs	8.5 hrs	5 hrs

Color Temperature: 4,000K

### ITEM NUMBERS

Description	UPC	Item #
Dualie 3AA Color-Rite - Includes (3) AA alkaline batteries - Yellow	080926-68910-7	68910

### BATTERY

- Uses (3) AA alkaline batteries; also accepts (3) AA lithium batteries

### MATERIAL/DURABILITY

- Durable, non-conductive, corrosion-proof polymer resin; rocky stipple texture for a sure grip
- Unbreakable polycarbonate face cap and side lens with scratch-resistant coating
- Rugged, integrated, snag-free clip (with optional magnet) conforms to body; grabs onto shirts, pockets and gear for hands-free use
- Magnet model features a magnetic clip with integrated hang hook for hands-free use
- IP67 dust-tight and waterproof to 1m for 30 minutes
- 2m impact resistance tested

### DIMENSIONS

**LENGTH:** 7 in (17.78 cm)  
**WEIGHT:** 6.8 oz (192.78g)  
 W/ BATTERIES





### SAFETY RATINGS

- Class I, II, Division 1, Groups A, B, C, D, E, F, G; Class III; T-Code: T4

### WARRANTY

Limited lifetime warranty  
 Visit [streamlight.com](http://streamlight.com) for full warranty information

**ACCESSORIES**

	Description	UPC	Item #
	Poly Mount Kit	080926-68089-0	68089
	4AA Fire Helmet Mount	080926-68085-2	68085
	4AA Gallet Mount	080926-68086-9	68086
	Rubber Helmet Band	080926-99075-3	99075