

# ENDURO<sup>®</sup> PRO

## LOW PROFILE, HIGH-PERFORMANCE, MULTI-FUNCTION HEADLAMP

Two red LEDs (yellow model) or Green LEDs (coyote model)



Model available with rubber strap and 3M<sup>®</sup> Dual Lock<sup>®</sup> fasteners for use on hard hats



Flood LED Spot LED -

Available Colors:

A low-profile, multi-function headlamp with the performance you've come to expect from Streamlight. Three lighting modes to cover a variety of tasks: spot beam for a focused beam, flood for soft area illumination that won't tire your eyes and red or green LEDs to preserve night vision.

## **KEY FEATURES**

- Lightweight, low-profile design
- 45° tilting head, especially handy for reading
- · Multi-fuction, push-button switch easy to use with gloves
- Yellow model features two red LEDs for low light visibility and the coyote model features two Green LEDs

#### OUTPUT

	SPOT			FLOOD		
	HIGH	MEDIUM	LOW	HIGH	MEDIUM	LOW
LUMENS	200	75	25	135	45	15
CANDELA	1,320	100		1,320	100	
DISTANCE	73m	20m		73m	20m	
RUN TIME	5 hrs	5 hrs	14 hrs	5 hrs	5 hrs	38 hrs

#### **ITEM NUMBERS**

Description	UPC	ltem #
Enduro Pro - Includes (3) AAA alkaline batteries, elastic headstrap - Clam - Yellow	080926-61420-8	61420
Enduro Pro - Includes (3) AAA alkaline batteries, elastic headstrap - Box - Yellow	080926-61421-5	61421
Enduro Pro - Includes (3) AAA alkaline batteries, elastic headstrap - Clam - Coyote	080926-61425-3	61425
Enduro Pro - Includes (3) AAA alkaline batteries, elastic headstrap, rubber hard hat strap and 3M® Dual Lock® - Box - Yellow	080926-61422-2	61422

## BATTERY

• Uses (3) AAA alkaline batteries (included); also accepts AAA lithium batteries

## MATERIAL/DURABILITY

- Tough, polycarbonate thermoplastic construction with elastomer over mold
- Unbreakable polycarbonate lenses
- IPX4 water-resistant
- 2m impact resistance tested

#### DIMENSIONS

**LENGTH:** 2.19 in (5.56 cm)

WEIGHT: 3.4 oz (96.38g) w/ alkaline // 3 oz (85.04g) w/ lithium

# WARRANTY

Limited lifetime warranty Visit streamlight.com for full warranty information