



Case Material: High-impact ABS thermoplastic housing. Rubberized impact bumper, lens ring and cushioned-grip handle. Toggle switch facilitates use with gloves

Dims/Weight: Length: 11.5 in. (29.2 cm) Width: 5.1 in. (13 cm) Height: 7 in. (17.8 cm) 7.9 lbs (3.58 kg) with battery (included in purchase)

Light Source: 3 shockproof C4® LEDs with a 50,000 hour lifetime. Jumper selectable high or low settings allow selection of more light output or more runtime.

Output/ User selectable high or low setting to allow higher light output or longer run time:

Run Time: - High: 540 lumens; 55,000 candela; 469m beam; runs 7 hours
- Low: 330 lumens; 32,000 candela; 358m beam; runs 15 hours

Battery: Zero-maintenance 6V, 12Ah sealed lead acid battery. Red and green LEDs give charge status feedback

Models: Standard System - International safety orange or high-visibility yellow; includes shoulder strap; includes AC/DC chargers and mounting rack; ideal for field maintenance, inspection of construction sites, and remote equipment.

Vehicle Mount System - International safety orange or high-visibility yellow; includes vehicle-mountable hard-wire rack and shoulder strap.

Approvals Most models meet applicable European Community Directives.
Charge rack meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position.

Warranty: Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. **THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW.** You may have other specific legal rights which vary by jurisdiction.

Item	UPC	Item #
E-Spot FireBox Standard System - IEC Type A (120V) AC/12V DC - shoulder strap & mounting rack - Orange	080926-45861-1	45861
E-Spot FireBox Standard System - IEC Type C (230V) AC/12V DC - shoulder strap & mounting rack - Orange	080926-45862-8	45862
E-Spot FireBox Standard System - IEC Type G (240V) AC/12V DC - shoulder strap & mounting rack - Orange	080926-45863-5	45863
E-Spot FireBox Standard System - IEC Type A (100V) AC/12V DC - shoulder strap & mounting rack - Orange	080926-45864-2	45864
E-Spot FireBox Vehicle Mount System - 12V DC - shoulder strap - Orange	080926-45865-9	45865
E-Spot FireBox (WITHOUT CHARGER) Orange	080926-45882-6	45882



#22060



#22061



#22062



#22051



#22050



#40163



#45072
#45074



#45070
#45071



#45845



#45937



#44050

Item		UPC	Item #
DC2 direct wire charge cord		080926-22050-8	22050
DC1 Charge Cord		080926-22051-5	22051
IEC Type C (230V) AC charge cord		080926-22061-4	22061
IEC Type A (100V/120V) AC charge cord		080926-22060-7	22060
IEC Type G (240V) AC charge cord		080926-22062-1	22062
Locking Device (keyed differently) *Must be factory installed		080926-40163-1	40163
Quick Release Strap		080926-44050-0	44050
Shoulder Strap		080926-45232-9	45232
Standard System Mounting Rack	Orange	080926-45070-7	45070
Direct Wire 12V DC Mounting Rack	Orange	080926-45071-4	45071
Standard System Mounting Rack	Yellow	080926-45072-1	45072
Direct Wire 12V DC Mounting Rack	Yellow	080926-45074-5	45074
Sealed Lead Acid Battery		080926-45937-3	45937
E-Spot Upgrade Kit		080926-45845-1	45845

