

SIDEWINDER[®] RESCUE

HANDS-FREE, MULTI-LED MILITARY LIGHT WITH TILTING HEAD



The Sidewinder Rescue is a slim, lightweight personal light that can be used as a life-saving beacon in times of distress or during swift water rescue operations. The 185° articulating head features a "slide-in-place" diffuser that projects omnidirectional light so you can be seen from almost anywhere.

KEY FEATURES

- Pull-to-turn locking rotary knob prevents accidental mode changes
- Push-button switch enables/disables selected lighting source starting at low intensity and progressing to the brightest intensity in 4 steps
- Double-click of button initiates high intensity strobe of selected light source
- Cord attachment holes provided in battery compartment cover capable of supporting 25 lbs of load
- Tethered battery compartment cap facilitates battery replacement in the dark without losing cap

	OUTPUT	LOW 5%	MED 1 25%	MED 2 60%	HIGH 100%	STROBE 100%
WHITE	55 lumens	100 hrs+	45 hrs	11 hrs	5.5 hrs	10 hrs
IR	25mw/sr (min) radiant intensity	200 hrs+	140 hrs	60 hrs	24 hrs	40 hrs
BLUE	1.8 lumens	150 hrs+	100 hrs	35 hrs	16 hrs	30 hrs
GREEN	4.5 lumens	150 hrs+	100 hrs	35 hrs	16 hrs	30 hrs

ITEM NUMBERS

OUTPUT

Description	UPC	Item #	NSN	
Sidewinder Rescue Kit - White, Green, Blue, IR LEDs - Includes MOLLE retainer, paracord and (2) AA alkaline batteries - Box	080926-14065-3	14065	6230-01-581-2486	

see reverse side for additional item numbers



Available Colors:

BATTERY

- (2) AA alkaline batteries (included) provide fast replacement with readily available batteries
- Lithium AA cells allow extended operation in extreme temperature environments (-40F to 150F)
- Tactile battery polarity indication on body allows replacement of cells in dark environment

MATERIAL/DURABILITY

- High impact super-tough nylon case offers exceptional durability and weather resistance
- All openings are O-ring sealed. Unbreakable polycarbonate lens with scratch-resistant coating. Gasket sealed
- IPX7 waterproof to 1m for 30 minutes

DIMENSIONS

HEIGHT:	2.34 in (4.94cm)
WEIGHT:	4.38 oz (124g) // ALKALINE 5.02 oz (142g)

WARRANTY

Streamlight warrants its Sidewinder (excepting batteries) will be free from manufacturing defects under normal use for 12 months after purchase. During the warranty period, at its sole discretion, Streamlight will repair or replace any defective part or product.

ITEM NUMBERS UPC Item # NSN Description Sidewinder Rescue Kit - White, Green, Blue, IR LEDs - Includes MOLLE retainer, paracord and (2) AA alkaline batteries - Clam 080926-14069-1 14069 -Sidewinder Rescue - White, Green, Blue, IR LEDs - Includes (2) AA alkaline batteries - Box 080926-14066-0 14066 -Sidewinder Rescue - White, Green, Blue, IR LEDs - Includes (2) AA alkaline batteries - Clam 080926-14067-7 14067 -Sidewinder Rescue - White, Green, Blue, IR LEDs - Includes E-mount and (2) AA alkaline 14068 080926-14068-4 _ batteries - Box

ACCESSORIES

	Description	UPC	Item #	NSN
	Helmet Mount	080926-14055-4	14055	5340-01-576- 8559
	Rail Mount for Helmet	080926-14057-8	14057	8470-01-633- 3996
	Elastic Headstrap	080926-14059-2	14059	6230-01-613-4313
	Night Vision Goggle Mount - Tactical (works with DoD, NATO, & ISAF combat helmets)	080926-14155-1	14155	
	Night Vision Goggle Mount - Aviation (works with HGU-84 rotary wing aircrew helmets)	080926-14135-3	14135	
	E-Mount (ACH, ECH, MICH, LWH compatible)	080926-14136-0	14136	5340-01-641-3930
	E-Mount Accessory Kit (Includes E-Mount, MOLLE Retainer and para- cord)	080926-14137-7	14137	
	Sidewinder Rescue Accessory Kit (Includes MOLLE Retainer and paracord)	080926-14304-3	14139	
	Helmet Mount Kit - Helmet Mount, Headstrap and MOLLE Plate	080926-14112-4	14112	
	Rail Mount Kit -Rail Mount, Headstrap and MOLLE plate	080926-14113-1	14113	8415-01-691-0048
19.00	Contour Arc Rail Mount	080926-14114-8	14114	
	Sidewinder High Offset ARC Rail Mount	080926-14115-5	14115	
	Hook and Loop Mount	080926-14073-8	14073	
3 3	MOLLE Retainer Replacement	080926-14030-1	14030	8415-01-691-0046
	Paracord	080926-14138-4	14138	
	Safety Wand - Glow in the Dark	080926-14902-1	14902	