



# SURVIVOR<sup>®</sup> ATEX



ATEX RATED RIGHT-ANGLE FLASHLIGHT



Available Colors: ●



Custom designed optic with optional, interchangeable Smoke-Cutter<sup>®</sup> plugs for preferred beam pattern:

- Black plug significantly reduces peripheral light for a tighter beam
- Amber plug reduces peripheral light and eye fatigue caused by glare

The Survivor ATEX features a low-profile bezel that doesn't interfere with gear or equipment. Its multi-fuel capability makes it easily interchangeable with different battery types. Lightweight design, because we understand that every ounce counts. Zone 0 gas and Zone 20 dust rated.

## KEY FEATURES

- Rubber dome push-button switch, easy to use with gloves
- Super strong, spring-loaded gear clip securely grabs onto turnout gear
- Specialized optic combines low profile with strong performance and wide beam

## OUTPUT

	HIGH	LOW
LUMENS	175	60
CANDELA	41,000	14,000
DISTANCE	405m	237m
RUN TIME <sup>Li-Ion</sup>	3.5 hrs	10 hrs
RUN TIME <sup>Alkaline</sup>	8 hrs	20 hrs

Flash for signaling: runs 5 hrs

Moonlight mode provides low-level lighting for battery conservation: runs 15 days

## ITEM NUMBERS

Description	UPC	Item #
Survivor - 230V AC/12V DC (ATEX)	080926-90562-7	90562
Survivor - 230V AC/12V DC (InMetro)	080926-90580-1	90580
Survivor - 240V AC/12V DC (ATEX)	080926-90563-4	90563
Survivor - 100V AC/12V DC (ATEX)	080926-90564-1	90564
Survivor - Without Charger (ATEX)	080926-90566-5	90566
Survivor - Without Charger (InMetro)	080926-90581-8	90581
Survivor - Alkaline (ATEX)	080926-90567-2	90567
Survivor - Alkaline (InMetro)	080926-90582-5	90582

## BATTERY

- Multiple power sources
- 6.2V, 1.5 Ah lithium-ion battery, rechargeable up to 1,500 times
- Optional (4) AA alkaline or (4) AA lithium batteries (requires battery carrier)

## MATERIAL/DURABILITY

- Housing, base, and battery made from high-impact, rugged nylon polymer body which is virtually indestructible
- Unbreakable polycarbonate lens with silicone anti-scratch coating
- One-way valve for case venting
- IP66 dust-tight and water-resistant
- 2m impact resistance tested

## DIMENSIONS

HEIGHT: 7.06 in (17.9 cm)

WEIGHT: <sup>LI-ION or ALKALINE</sup> 13.7 oz (388g) // <sup>AA LITHIUM</sup> 12.5 oz (354g)  
W/ BATTERIES

## SAFETY RATINGS

- Ex: FTZU 15 ATEX 0046X; IEC Ex FTZU 15.0029X  
II 1G Ex ia op is IIB T3/T4 Ga; II 2G Ex ia op is IIC T3/T4 Gb
- INMETRO: Ex ia op is IIB T3/T4 Ga; Ex ia op is T3/T4 Gb
- Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position
- Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018)

## WARRANTY

Limited lifetime warranty  
Visit [streamlight.com](http://streamlight.com) for full warranty information

ACCESSORIES

	Description	UPC	Item #
	5-Unit 120V AC Bank Charger 5-Unit 230V AC Bank Charger 5-Unit 12V DC Bank Charger	080926-90910-6 080926-90911-3 080926-90912-0	90910 90911 90912
	Battery Carrier (for alkaline models) <i>Batteries not included</i>	080926-90542-9	90542
	Charger Holder	080926-90345-6	90345
	Lithium-Ion Battery Pack	080926-90316-8	90316
	240V AC (AUS/NZ) Charge Cord	080926-22048-5	22048
	12V DC2 Charge Cord	080926-22050-8	22050
	12V DC1 Charge Cord	080926-22051-5	22051
	120V AC Charge Cord	080926-22060-7	22060
	230V AC Charge Cord	080926-22061-4	22061
	240V UK AC Charge Cord	080926-22062-1	22062
	Smoke Cutter Plug Kit	--	908019