



SURVIVOR PIVOT[®] USB

DUAL-BEAM, USB RECHARGEABLE FLASHLIGHT





Spring-loaded clip
Optional magnet available



Battery status indicator in switch:

- Green indicates full charge
- Turns red when battery is nearing low voltage
- Flashes red continuously when 15 minutes left of battery life



Available Colors:  

The multi-function Survivor Pivot USB provides budget-friendly rechargeability combined with a dual beam and 90-degree articulating head. Its spot beam uses a cool white, high-power LED for maximum distance illumination and its flood beam is angled downward for area illumination.

KEY FEATURES

- 90° articulating head aims the beam where you need it
- Translucent switch boot with integrated battery status indicator
- Multiple options for clipping or hanging on your gear

OUTPUT

	SPOT		FLOOD		COMBO	
	HIGH	LOW	HIGH	LOW	HIGH	LOW
LUMENS	300	70	300	70	325	80
CANDELA	34,000	8,500	300	75	19,000	5,000
DISTANCE	369m	184m	35m	17m	276m	141m
RUN TIME ^{SL-B26}	4.25 hrs	16 hrs	4.25 hrs	16 hrs	3.75 hrs	13 hrs
RUN TIME ^{Alkaline}	5.5 hrs	15 hrs	5.5 hrs	15 hrs	4.5 hrs	12 hrs

ITEM NUMBERS

Description	UPC	Item #
Survivor Pivot USB - Orange	080926-91804-7	91804
Survivor Pivot USB - Yellow	080926-91814-6	91814
Survivor Pivot USB - Magnet - Orange	080926-91838-2	91838
Survivor Pivot USB - Magnet - Yellow	080926-91839-9	91839

BATTERY

- Multi-Fuel: Uses (1) rechargeable SL-B26[®] lithium-ion battery pack; also accepts (3) AA alkaline batteries
- SL-B26 battery pack charges in 5 hours
- Battery status indicator

MATERIAL/DURABILITY

- Housing and base made from high-impact, super tough nylon
- Spring-loaded clip with built-in D-ring easily attaches to belts and harnesses and reduces unwanted rotation
- One-way valve for case venting
- IP67 dust-tight and waterproof to 1m for 30 minutes

DIMENSIONS

HEIGHT: 7.93 in (20.14 cm)
WEIGHT: SL-B26 15.8 oz (448g) // ALKALINE 16.7 oz (473g)
WEIGHT: SL-B26 17.2 oz (488g) // ALKALINE 18.1 oz (513g)
 W/ MAGNET

SAFETY RATINGS

- Class I & II, Division 2, Groups A, B, C, D, F, G; Class III, T-Code: T4 only with Streamlight 220115

WARRANTY

Limited lifetime warranty
 Visit streamlight.com for full warranty information

ACCESSORIES

	Description	UPC	Item #
	SL-B26 Charger Kit w/ USB Cord	080926-22010-2	22010
	SL-B26 Charger Kit w/ 120V AC Adapter	080926-22011-9	22011
	SL-B26 Battery Pack - 1 Pack SL-B26 Battery Pack - 2 Pack SL-B26 Battery Pack - 8 Pack	080926-22101-7 080926-22102-4 080926-22105-5	22101 22102 22105
	Battery Carrier (for alkaline and SL-B26 models) <i>Batteries not included</i>	080926-90342-5	90342
	40" (101.6 cm) USB cord 22" (55.88 cm) USB cord	080926-22070-6 080926-22081-2	22070 22081
 <p>BATTERIES NOT INCLUDED</p>	8-Unit SL-B26 Bank Charger - 12V DC 8-Unit SL-B26 Bank Charger - 120V/100V AC 8-Unit SL-B26 Bank Charger - 230V/240V AC	080926-20220-7 080926-20221-4 080926-20222-1	20220 20221 20222
 <p>BATTERIES INCLUDED</p>	8-Unit SL-B26 Bank Charger - 12V DC 8-Unit SL-B26 Bank Charger - 120V/100V AC 8-Unit SL-B26 Bank Charger - 230V/240V AC	080926-20223-8 080926-20224-5 080926-20225-2	20223 20224 20225
	Magnet Accessory Kit (<i>magnet only, clip not included</i>)	080926-91840-5	91840