

## VANTAGE® 180 X USB // VANTAGE® 180 X **MULTI-FUEL, MULTI-FUNCTION** HELMET/RIGHT-ANGLE FLASHLIGHT







to aim the beam

Includes "quick release" helmet bracket and hex key

Material/Lens High-impact, super tough nylon. Chemical-resistant engineering polymer for exceptional durability and sure grip. Unbreakable polycarbonate lens with a silicone anti-scratch coating. O-ring sealed. Available in safety orange or black.

Dims/Weight	IMPERIAL	MPERIAL HEIGHT: 5.20 in HEAD DIAMETER: 1.60 in BODY: 1.06 in WEIGHT with SL-B26 BATTERY PAC		WEIGHT WITH SL-B26 BATTERY PACK: 5.9 OZ	WEIGHT WITH CR123A BATTERIES: 5.5 OZ	
	METRIC	HEIGHT: 13.2 cm	HEAD DIAMETER: 4.06 cm	BODY: 2.69 cm	WEIGHT with sl-b26 battery pack: 167 g	WEIGHT WITH CR123A BATTERIES: 156 g

Light Source White LED, impervious to shock with a 50,000-hour lifetime. Rear light: Ultra-bright blue safety taillight or white safety flood downlight.

**Output/Run Time** 

	HIGH	LOW
LUMENS	250	100
CANDELA	7,200	2,650
DISTANCE	170 m	103 m
RUN TIME (SL-B26)	5 hours	15 hours
RUN TIME (CR123A)	4 hours	12 hours

- Switch Body-mounted push-button switch provides one-handed "constant on" operation. Fast double-click for low mode. Rotate head 90 degrees towards push-button to automatically change rear LED from blue safety taillight to white safety downlight.
- Battery Multi-fuel: Uses one (1) Streamlight SL-B26® protected Li-Ion rechargeable battery pack; also accepts two (2) CR123A lithium batteries. WARNING - EXPLOSION RISK, BURN, AND FIRE HAZARD. Do not use SL-B9<sup>TM</sup> batteries in firefighting apparatus or fire situations. Do not expose SL-B9<sup>TM</sup> battery to temperatures greater than 140 °F (60 °C).
- Features 180° rotating head automatically changes blue taillight to white downlight
  - Helmet bracket (included with purchase) features quick release to detach light
  - Turnout gear attachment hook
  - 1m impact resistance tested; IPX7-rated design; waterproof to 1m for 30 minutes
- Approvals Meets applicable United Kingdom and European Community Directives. Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018). CEC Compliant (USB model only).
- Warranty Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse, and normal wear. We will repair, replace, or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches, and electronics which have a 2-year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANT-ABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit streamlight.com for full warranty information.

Description	UPC	Item #
Vantage 180 X – Includes two CR123A lithium batteries and helmet bracket - Box - Orange	080926-88901-9	88901
Vantage 180 X – Includes two CR123A lithium batteries and helmet bracket - Box - Black	080926-88903-3	88903
Vantage 180 X USB – Includes one SL-B26 battery pack and helmet bracket - Box - Orange	080926-88911-8	88911
Vantage 180 X USB – Includes one SL-B26 battery pack and helmet bracket - Box - Black	080926-88913-2	88913

	Description	UPC	ltem #
	40" (101 cm) Micro-USB Cord	080926-22070-6	22070
	22" (55.88 cm) Micro-USB Cord	080926-22081-2	22081
	240V AC USB Plug	080926-22049-2	22049
	Y-Split USB Cord	080926-22082-9	22082
	Li-Ion USB Battery Charger	080926-22100-0	22100
	SL-B26 USB Charger Kit (Includes two SL-B26 battery packs)		22010
	SL-B26 Charger Kit - 120V AC (Includes two SL-B26 battery packs)	080926-22011-9	22011
	SL-B26 Battery Pack - 2 PK SL-B26 Battery Pack - 8 PK	080926-22102-4 080926-22105-5	22102 22105
() ()	Lithium Batteries - 2 PK	080926-85175-7	85175
רופאני	Lithium Batteries - 6 PK	080926-85180-1	85180
REAM	Lithium Batteries - 12 PK	080926-85177-1	85177
	Lithium Batteries - 400 PK	080926-85179-5	85179