



SURVIVOR® RIGHT ANGLE LIGHT :: RECHARGEABLE OR ALKALINE

Safety-Rated Firefighter's Right Angle Light

The Survivor features a low-profile bezel that doesn't interfere with gear and equipment and provides four lighting modes. The clip securely grabs onto gear, and the D-ring allows your light to hang forward.

Class 1, Div. 1 rated

- [Click here for data sheet](#)
- Available in **Rechargeable and Alkaline models**
- LED technology with four lighting modes:
 - Rechargeable model
 - High for a super-bright beam that pierces through smoke: 175 lumens; 405m beam distance; runs 3.5 hours
 - Low for bright light and longer run time: 60 lumens; 237m beam distance; runs 13 hour
 - Flash for signaling: runs 8 hours
 - Moonlight mode provides low-level lighting for battery conservation: runs 20 days
 - Alkaline model
 - High for a super-bright beam that pierces through smoke: 175 lumens; 405m beam distance; runs 4 hours
 - Low for bright light and longer run time: 60 lumens; 237m beam distance; runs 15 hours
 - Flash for signaling: runs 8 hours
 - Moonlight mode provides low-level lighting for battery conservation: runs 20 days
- Custom designed optic with optional, interchangeable Smoke Cutter plugs for preferred beam pattern:
 - Black plug significantly reduces peripheral light for a tighter beam
 - Amber plug reduces peripheral light and eye fatigue caused by glare
- Strong spring-loaded clip securely grabs onto belts and gear; D-ring features forward-hanging orientation
- Optimized electronics provide regulated intensity
- Rechargeable NiMH battery can be recharged up to 1,000 times. Also accepts four (4) AA alkaline batteries
 - * 230V / 240V configurations with NiMH battery are not Class 1, Div. 1 rated
- Rubber dome push-button switch provides easy operation even when wearing heavy gloves
- High-impact super-tough nylon construction offers exceptional durability; O-ring sealed, unbreakable polycarbonate lens with silicone anti-scratch coating is assembled in a heavy-duty bezel
- IPX4 water-resistant; 2-meter impact resistance tested
- Serialized for positive identification
- H x W: 7.06 in x 2.85 in (17.92 x 7.24 cm) — Height in charger: 8.67 in (22.02 cm)
- Weight: Rechargeable - 18.0 oz (510 g); Alkaline - 13.7 oz (388 g)
- Available in orange, yellow, or black
- Assembled in the USA
- THE PRODUCT SPECIFICATIONS BELOW REFER TO THE RECHARGEABLE MODEL ONLY

PRODUCT SPECIFICATIONS

High Lumens

175

Run Time

3.50

Run Time

13.00

Beam Distance

405

Max Candela

41,000

Battery Type

Nickel-Metal Hydride, AA Alkaline

Length

7.06 inches (17.93 centimeters)

Weight

1 pounds 2.00 ounces (510.29 grams)

Colors

Orange, Yellow, Black